## SAFETY DATA SHEET

SECTION I: I	DENTIF	ICATION								
PRODUCT	ITP BACKER ROD			MANUFACTURER NAME & ADDRESS:						
IDENTIFIER:					INDUSTRIAL THERMO POLYMERS					
CHEMICAL	POLYETH	POLYETHYLENE			(Owned and Operated by Armacell Canada Inc.)					
IDENTITY:					153 VAN KIRK DR					
		GING, CUSHIONING, SOUND DAMI		PENING,	BRAMPTON, ONT	ARIO, LIA				
	INSULATION, SEALING, FLOATATION etc.				PHONE NO.: FAX NO.:		1-905-846-3666 1-905-846-0363			
RESTRICTION OF	NONE				EMERGENCY PHONE NO.:		1-905-846-0363			
						1-000-001-00-41				
SECTION 2 : HAZARD(S) IDENTIFICATION										
<ul> <li>POLYETHYLENE EXTRUDED FOAM PRODUCTS ARE CLASSIFIED BY OSHA AS "NON HAZARDOUS".</li> </ul>										
- PE_FOAM PRODUCTS ARE MADE FROM_POLYETHYLENE RESIN , ADDITIVES AND ISOBUTANE .(MORE DETAILS IN SEC.3.)										
- ISOBUTANE, A F	LAMABLE	HYDROCARBON IS	S USED AS	BLOWIN	G AGENT.SMALL T	RACES OF	THIS GAS MAY BE			
PRESENT IN THE F	PRODUCT	. THIS GAS MAY AC	CCUMULAT	TE AT HAZ	ZARDOUS CONCE	NTRATIONS	S ABOVE THE LOWER			
FLAMMABLE LIMIT	S (LFL) IF	LARGE QUANTITIE	S OF THIS	S PRODUC	CT ARE STORED IN	I UNVENTIL	_ATED AREAS.			
ROUTES OF	SWALLO	WING SKIN AB	SORBTION	J	INHALATION	SKIN CO	NTACT EYE CONTACT			
EXPOSURE:		Г		•	$\checkmark$					
EFFECTS OF A SIN			JRE BY:							
SWALLOWING:	<u></u>	CHOKING - MECH		OCKAGE						
SKIN ABSORBTIO	N:	NOT LIKELY.								
INHALATION:		FOAM DUST MAY	CAUSE RE		TO NOSE THROAT		S			
SKIN CONTACT:		NON IRRITATING					0.			
EYE CONTACT:		EYE INJURY OR F				O EVES				
OTHER EFFECTS		NOT KNOWN				0 2 1 2 5				
UTHER EFFECTS										
SECTION 3 : CO					170					
SECTION 3 : COI	MPUSITI			GREDIEI	1					
INGREDIEN	TS			GHT %						
					ACGIH - TLV*					
POLYETHYL		9002-88-4	75% -100%		NA 800 PPM TWA					
ISOBUTANE		75-28-5	-							
CARBON BL	ACK	1333-86-4	<b>0%</b> ·	- 5%		3.5 m	ng/m <sup>3</sup>			
* Applicable provincial	TLV's may	differ								
* Specific chemical nat	mes and pe	rcentage in the mix has	s been withh	eld to prote	ct trade secret.					
SECTION 4 : FIR	ST AID M	IEASURES								
SWALLOWING:			SKIN CONTACT:							
CONSULT PHYSICIAN				WASH WITH SOAP AND WATER						
INHALATION:				EYE CONTACT:						
MOVE TO FRESH	AIR. SEEK	K MEDICAL ATTENT	ION IF	FLUSH EYES WITH CLEAN LUKEWARM WATER. CONSULT						
BREATHING PROBLEMS PEI				PHYSICIAN.						
SECTION 5 : F	IRE FIC	HTING MEAS	URES							
				OSED TO	SPARKS OR OPE	N FLAME. F	RESULTS IN CLASS A FIRE.			
							TER TO COOL AND SMOTHER			
2. TIKE TO BE EXTIN	COUCHED	DI CONCONATENTA			SOAR THE I RODOO		IER TO COOL AND DIMOTHER			

3. FIRE WILL CAUSE DENSE SMOKE. USE SELF-CONTAINED BREATHING APPRATUS AND FULL PROTECTIVE CLOTHING.

4. FIRE WILL RESULT IN INTENSE HEAT AND SMOLDERING. EXTINGUISHMENT IS BY COOLING WITH WATER.

5. OTHER FIRE EXTINGUISHERS (DRY CHEMICAL, FOAM OR CO2 EXTINGUISHERS) MAY BE USED FOR EXTINGUISHMENT. 6. CHEMICAL/GASEOUS HAZARDS LIKE CO, CO2 AND CARBON MAY BE PRODUCED FROM THE SMOLDERING SUBSTANCES AND FIRE.

# SAFETY DATA SHEET

## SECTION 6: ACCIDENTAL RELEASE MEASURES

PE FOAM IS COMBUSTIBLE. SHOULD NOT BE EXPOSED TO SPARKS OR OPEN FLAME. RESULTS IN CLASS 'A' FIRE.

## **SECTION 7: HANDLING AND STORAGE**

- PE FOAM IS COMBUSTIBLE AND SHOULD NOT BE EXPOSED TO SPARKS OR OPEN FLAME. WHEN BURNS, WILL RELEASE TOXIC GASES LIKE CO .

-WHEN FABRICATING OR CUTTING , THIS PRODUCT MAY RELEASE TRAPPED ISOBUTANE FROM THE FOAM CELLS. ADEQUATE VENTILATION IS A MUST.

- PE FOAM SHOULD BE STORED IN COOL, DRY AND WELL VENTILATED LOCATIONS. ISOBUTANE GAS MAY ACCUMULATE AROUND THE PRODUCT.

- PE FOAM IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS LIKE, CL2 ,H2O2 , KNO3 ,H2SO4.

### SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

- NOT NECESSARY OTHER THAN STATED IN SECTION 2

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SOLID	FREEZING POINT:	N/A	SPECIFIC GRAVITY VAPOUR	N/A		
N/A	VAP. PRESS at 20°C:	N/A	MOLECULAR WEIGHT:	N/A		
0.01 - 0.15	SOLUBILITY IN WATER	INSOLUBLE	COEFFICIENT OF WATER /	N/A		
+ 212°F	EVAPORATION RATE	N/A	OIL DISTRIBUTION:	N/A		
0-30 lbs/cuft	% VOLATILES BY VOLUME:	N/A	VAPOUR DENSITY	N/A		
CLOSED CELL FOAM	ODOR:	NEGLIGIBLE	ODOR THRESHOLD:	N/A		
	N/A 0.01 - 0.15 + 212°F 0-30 lbs/cuft	N/A         VAP. PRESS at 20°C:           0.01 - 0.15         SOLUBILITY IN WATER           + 212°F         EVAPORATION RATE	N/A         VAP. PRESS at 20°C:         N/A           0.01 - 0.15         SOLUBILITY IN WATER         INSOLUBLE           + 212°F         EVAPORATION RATE         N/A           0-30 lbs/cuft         % VOLATILES BY VOLUME:         N/A	N/A     VAP. PRESS at 20°C:     N/A     MOLECULAR WEIGHT:       0.01 - 0.15     SOLUBILITY IN WATER     INSOLUBLE     COEFFICIENT OF WATER /       + 212°F     EVAPORATION RATE     N/A     OIL DISTRIBUTION:       0-30 lbs/cuft     % VOLATILES BY VOLUME:     N/A     VAPOUR DENSITY		

## SECTION 10 : STABILITY AND REACTIVITY

- PE FOAM IS STABLE AND NON-REACTIVE. OTHER THAN CONDITIONS STATED IN SECTION 5 ,6 & 7

### SECTION 11 : TOXICOLOGICAL INFORMATION

- PE FOAM HAS NO CARCINGENIC SUBSTANCES. IT IS NOT LISTED IN : IARC & NTP

ROUTES OF EXPOSURE : SWALLOWING FOAM DUST INHALATION SKIN CONTACT EYE CONTACT EFFECTS OF ABOVE EXPOSURE STATED IN SECTION 4

### **SECTION 12 : ECOLOGICAL INFORMATION**

- PE FOAM DOES NOT EXHIBIT ANY SIGNIFICANT BIODEGRADATION.

## SECTION 13 : DISPOSAL CONSIDERATIONS

- PE FOAM CAN BE REPROCESSED OR CAN BE DISPOSED OFF IN LANDFILL

#### **SECTION 14 : TRANSPORT INFORMATION**

- PE FOAM HAS SOME RESIDUAL ISOBUTANE AND HENCE TO BE TRANSPORTED IN VENTILATED TRAILERS.

### SECTION 15 : REGULATORY INFORMATION

- PE FOAM HAS NO CARCINGENIC SUBSTANCES AND IS CLASSIFIED AS NON HAZARDOUS UNDER THE FEDERAL OSHA STANDARDS.

### **SECTION 16 : OTHER INFORMATION**

PREPARED BY / DEPARTMENT	PHONE NUMBER	DATE UPDATED
HARENDRA RATHOD / QA DEPARTMENT	905-846-3666 / 1-800-387-3847	April 16, 2015

FOR INFORMATION : Visit Web: www.tundrafoam.com or Email: info@tundrafoam.com