# SAFETY DATA SHEET



Issue Date 25-Mar-2016 Revision Date 27-Aug-2021 Version 2

### 1. IDENTIFICATION

Product identifier

Product Name Air-Bloc 17MR

Other means of identification

Product Code HE017 Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Coatings

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressHENRY COMPANYHENRY COMPANY

15 Wallsend Dr. 999 N. Pacific Coast Hwy., Suite 800

Scarborough, ON M1E 3X6 El Segundo, CA 90245-2716

Canada Web Site: www.henry.com www.ca.henry.com

Web Site: www.henry.com www.ca.henry.com

**Emergency telephone number** 

Company Phone Number 800-486-1278

Emergency Telephone US and Canada only (toll-free): 3E Company - 1-866-519-4752 (access code 334832)

US/Canada, all other countries: 3E Company - +1-760-476-3962 (access code 334832) Mexico (additional contact option): 3E Company - +52 55 41696225 (Code 334832)

# 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin corrosion/irritation                        | Category 2  |
|--|-------------|
| Serious eye damage/eye irritation                | Category 2A |
| Specific target organ toxicity (single exposure) | Category 3  |

# Label elements

### **Emergency Overview**

### Warning

#### **Hazard statements**

Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation

•



Appearance viscous cream

# Physical state liquid

Odor Slight

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

# **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Toxic to aquatic life with long lasting effects. Toxic to aquatic life.

### **Unknown acute toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Not applicable

#### Mixture

| Chemical Name                               | CAS No      | Weight-% |
|---|-------------|----------|
| Water *                                     | 7732-18-5   | 15 - 40  |
| Limestone *                                 | 1317-65-3   | 15 - 40  |
| Acrylic polymer (non-hazardous) *           | Proprietary | 10 - 30  |
| Asphalt *                                   | 8052-42-4   | 1 - 5    |
| Ethylene glycol *                           | 107-21-1    | 1 - 5    |
| Non-phthalate Plasticizer (non-hazardous) * | Proprietary | 1 - 5    |
| Titanium dioxide *                          | 13463-67-7  | 1 - 5    |
| Diethylene glycol monobutyl ether *         | 112-34-5    | 1 - 5    |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible). If symptoms persist, call a physician.

**Eye contact** Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial

flushing, remove any contact lenses and continue flushing for at least 15 minutes. If

symptoms persist, call a physician.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing

before reuse.

**Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If

symptoms persist, call a physician.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting without

medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.

**Self-protection of the first aider**Use personal protective equipment as required.

### Most important symptoms and effects, both acute and delayed

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians**Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media No information available.

### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

# **Explosion data**

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Use personal protective

equipment as required. Avoid contact with skin, eyes or clothing.

**Environmental precautions** 

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. Do not flush into

surface water or sanitary sewer system.

# Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Cover liquid spill with sand, earth or other

non-combustible absorbent material. Dam up. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children.

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

| Chemical Name                              | ACGIH TLV   | OSHA PEL  | NIOSH IDLH   |
|--|---|---|--|
| Limestone<br>1317-65-3                     | -   | TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction | TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust  |
| Asphalt<br>8052-42-4                       | TWA: 0.5 mg/m³ benzene-soluble aerosol fume, inhalable particulate matter | -   | Ceiling: 5 mg/m³ fume 15 min   |
| Ethylene glycol<br>107-21-1                | TWA: 25 ppm (vapor fraction)<br>STEL: 50 ppm (vapor fraction)             | -   | -  |
| Titanium dioxide<br>13463-67-7             | TWA: 10 mg/m³   | TWA: 15 mg/m³ total dust                                  | IDLH: 5000 mg/m³<br>TWA: 2.4 mg/m³ CIB 63 fine<br>TWA: 0.3 mg/m³ CIB 63 ultrafine,<br>including engineered nanoscale |
| Diethylene glycol monobutyl ether 112-34-5 | TWA: 10 ppm inhalable fraction and vapor                                  | -   | -  |

NIOSH IDLH Immediately Dangerous to Life or Health

### **Appropriate engineering controls**

Engineering Controls Showers

Eyewash stations Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** 

Handle in accordance with good industrial hygiene and safety practice.

@ 40 °C

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state liquid

Appearance viscous cream Odor Slight

Color Light gray Odor threshold No information available

Property Values Remarks • Method

**pH** 6-9

Melting point / freezing point  $\leftarrow 0 \, ^{\circ}\text{C} \, / \, 32 \, ^{\circ}\text{F}$ 

Boiling point / boiling range > 100 °C / 212 °F

Flash point > 100 °C / 212 °F Pensky-Martens Closed Cup (PMCC)

Evaporation rate >= 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Vapor pressure 18 mmHg @ 25 °C

Vapor density No information available

Relative density 1.1-1.3 Water solubility dispersible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
No information available
No information available
No information available

Kinematic viscosity > 100 mm2/s

**Dynamic viscosity**No information available

Explosive properties

Oxidizing properties

Not an explosive
Not applicable

**Other Information** 

Softening point
Molecular weight
VOC Content (%)
Density
No information available

# 10. STABILITY AND REACTIVITY

Reactivity

No data available

**Chemical stability** 

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions** 

None under normal processing.

Conditions to avoid

Elevated Temperature. Keep from freezing. Incompatible materials.

**Incompatible materials** 

Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous Decomposition Products** 

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

# 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

#### **Product Information**

**Inhalation** May cause irritation of respiratory tract.

Eye contact Irritating to eyes.

Skin contact Irritating to skin.

**Ingestion** Based on available data, the classification criteria are not met.

| Chemical Name                              | Oral LD50           | Dermal LD50                                 | Inhalation LC50          |
|--|---------------------|---|--------------------------|
| Water<br>7732-18-5                         | > 90 mL/kg(Rat)     | -   | -                        |
| Asphalt<br>8052-42-4                       | > 5000 mg/kg (Rat)  | > 2000 mg/kg(Rabbit)                        | > 94.4 mg/m³ (Rat) 4.5 h |
| Ethylene glycol<br>107-21-1                | = 4700 mg/kg (Rat)  | = 10600 mg/kg (Rat)= 9530 μL/kg<br>(Rabbit) | -                        |
| Titanium dioxide<br>13463-67-7             | > 10000 mg/kg (Rat) | -   | -                        |
| Diethylene glycol monobutyl ether 112-34-5 | = 5660 mg/kg (Rat)  | = 2700 mg/kg ( Rabbit )                     | -                        |

# Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization**Based on available data, the classification criteria are not met. **Germ cell mutagenicity**Based on available data, the classification criteria are not met.

Carcinogenicity This product contains titanium dioxide which is classified as a possible carcinogen when

present as respirable dust. This is not relevant for this product since it is a liquid. The table

below indicates whether each agency has listed any ingredient as a carcinogen.

|                                |       |          | <u>, , , , , , , , , , , , , , , , , , , </u> |      |
|--------------------------------|-------|----------|---|------|
| Chemical Name                  | ACGIH | IARC     | NTP   | OSHA |
| Asphalt<br>8052-42-4           | -     | Group 2B | -   | X    |
| Titanium dioxide<br>13463-67-7 | -     | Group 2B | -   | X    |

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Based on available data, the classification criteria are not met.

**STOT - single exposure** Target Organs. Respiratory system. Eyes.

STOT - repeated exposure
Target Organ Effects
Aspiration hazard

Based on available data, the classification criteria are not met.
Eyes, lungs, Respiratory system, Skin, Central nervous system.
Based on available data, the classification criteria are not met.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 10,348.00 mg/kg

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

None known

### Persistence and degradability

No information available.

#### **Bioaccumulation**

| Chemical Name               | Partition coefficient |
|-----------------------------|-----------------------|
| Asphalt<br>8052-42-4        | >6                    |
| Ethylene glycol<br>107-21-1 | -1.93                 |

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

# 14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedIATANot regulatedIMDGNot regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name                                | SARA 313 - Threshold Values % |  |
|--|-------------------------------|--|
| Ethylene glycol - 107-21-1                   | 1.0                           |  |
| Diethylene glycol monobutyl ether - 112-34-5 | 1.0                           |  |

#### SARA 311/312 Hazard Categories

Acute health hazardYesChronic Health HazardNoFire hazardNoSudden release of pressure hazardNoReactive HazardNo

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name   | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|-----------------|--------------------------|----------------|--------------------------|
| Ethylene glycol | 5000 lb                  | -              | RQ 5000 lb final RQ      |
| 107-21-1        |                          |                | RQ 2270 kg final RQ      |

### **US State Regulations**

#### **California Proposition 65**

This product contains titanium dioxide which is classified as an IARC 2B carcinogen based on laboratory studies where animals were exposed to titanium dioxide dust. This is not a relevant route of exposure for this product since it is a moist solid material with little to no chance of producing dust This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product

| Chemical Name                 | California Proposition 65 |  |
|-------------------------------|---------------------------|--|
| Titanium dioxide - 13463-67-7 | Carcinogen                |  |
| Quartz - 14808-60-7           | Carcinogen                |  |

### U.S. State Right-to-Know Regulations

| Chemical Name                              | New Jersey | Massachusetts | Pennsylvania |
|--|------------|---------------|--------------|
| Limestone<br>1317-65-3                     | Х          | X             | X            |
| Asphalt<br>8052-42-4                       | Х          | X             | X            |
| Ethylene glycol<br>107-21-1                | Х          | X             | X            |
| Titanium dioxide<br>13463-67-7             | Х          | X             | X            |
| Diethylene glycol monobutyl ether 112-34-5 | Х          | -             | X            |
| Sulfur<br>7704-34-9                        | Х          | Х             | X            |
| Quartz<br>14808-60-7                       | Х          | X             | X            |

# U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 0 Instability 0 Physical and Chemical

Properties HMIS Health hazards 2 Flammability 0 Physical hazards 0 Personal protection X

Issue Date 25-Mar-2016 Revision Date 27-Aug-2021

Revision Note

No information available

**Disclaimer** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**