Revision Date: 06-08-2015 Product Code: FC7510

### 1. IDENTIFICATION

Product Name WEAR COAT & NON-UV TOPCOAT GRAY

Product Code FC7510 Document ID GFC7510

Revision Number 1 Prior Version Date None

Industrial Maintanance Floor TopCoat

Restrictions On Use For Industrial Use Only Chemical Family Urethane Coating

Chemical Manufacturer / Importer NEOGARD® - a Division of JONES-BLAIR® Company, LLC

2728 Empire Central Dallas, TX 75235 1-214-353-1600

Emergency Telephone Number: ChemTrec Center 1-800-424-9300

International: 703-527-3887

### 2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

### **Hazard Pictograms**



GHS Classification Serious Eye Damage/Eye Irritation Category 2B

Carcinogenicity Category 2

Signal Word Warning

**Hazard Statements** Causes eye irritation Suspected of causing cancer.

**Precautionary Statements** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Wash thoroughly after handling. Use personal

protective equipment as required.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. IF exposed or concerned:

Get medical attention. If eye irritation persists: Get medical attention.

Storage Store locked up.

**Disposal** Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazards Not Otherwise Classified (HNOC)

Not applicable

Revision Date: 06-08-2015 Product Code: FC7510

#### **Additional Information**

Not applicable

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Component	CAS#	<u>%</u>	
Castor oil	8001-79-4	40 - 60	
Titanium dioxide	13463-67-7	3 - 7	
Crystalline Aluminosilicate	1318-02-1	1 - 5	
Quartz (Silica-Crystalline)	14808-60-7	0.1 - 1	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST-AID MEASURES

**Inhalation** Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen.

**Eye Contact** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Get medical attention immediately.

**Skin Contact** Wash with soap and water. Get medical attention if irritation develops or persists.

**Ingestion** If swallowed, do not induce vomiting. Get medical attention immediately.

Most Important Acute Symptoms Not Available

and Effects

Most Important Delayed Symptoms

and Effects

Symptoms Not Available

**Special treatment needed:**No additional first aid information available

### 5. FIRE-FIGHTING MEASURES

involving this material. Carbon dioxide Alcohol foam Dry chemical

Water spray

Unsuitable Extinguishing Media

Fire and/or Explosion Hazards

No data available

Material may be ignited only if preheated to temperatures above the

high flash point, for example in a fire.

**Special Protective Equipment and Precautions for Fire-Fighters** 

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Do not enter fire

area without proper protection including self- contained breathing

apparatus and full protective equipment.

Will not burn, no special instructions available. Use methods

appropriate for surrounding materials.

### **6. ACCIDENTAL RELEASE MEASURES**

Personal Precautions, Protective Equipment and Emergency Procedures

Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the

material spilled, the quantity of the spill, the area in which the spill occurred. See MSDS sections III, XIII and XV for disposal

considerations.

**Methods and Material for Containment** 

and Cleaning Up

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material.

Gather and store in a sealed container pending disposal.

**Revision Date: 06-08-2015** Product Code: FC7510

7. HANDLING AND STORAGE

**Precautions for Safe Handling** Harmful or irritating material. Avoid contacting and avoid breathing the

material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this

material.

**Conditions for Safe Storage** 

Materials to Avoid/Chemical

Incompatibility

Store in a cool dry place. Keep container(s) closed.

Oxidizing agents

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Limits**

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Limestone	15 mg/m³ (total dust); 5 mg/m³ (respirable fraction)		
Titanium dioxide	15 mg/m³ TWA (total dust)	10 mg/m³ TWA	
Quartz (Silica-Crystalline)	see Table Z-3	0.05 mg/m³ TWA (respirable fraction)	

**Appropriate** Local exhaust ventilation or other engineering controls may be required when handling or

**Engineering Controls** using this product to avoid overexposure.

**Respiratory Protection** General or local exhaust ventilation is the preferred means of protection. In cases where

ventilation is inadequate, respiratory protection may be required to avoid overexposure.

Follow respirator manufacturer's directions for respirator use.

No data available / No data available

**Eye Protection** Wear safety glasses with side shields when handling this product.

**Skin Protection** Where use can result in skin contact, practice good personal hygiene. Wash hands and

other exposed areas with mild soap and water before eating, drinking, and when leaving

work. Clothing suitable to prevent skin contact.

**General Hygiene** As with all chemicals, good industrial hygiene practices should be followed when

**Conditions** handling this material.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

**Physical State** Liquid Color Grev

Odor No data available **Odor Threshold** No data available No data available

Melting Point/Freezing Point (°F/°C)

**Initial Boiling Point and Boiling Range** 

Low (°F) No data available

Flash Point (°F/°C) 205 / 96

Flammability (solid, gas) No data available **Upper Flammable/Explosive Limit** No data available Lower Flammable/Explosive Limit No data available **Vapor Density** No data available

**Relative Density** 0.960

Solubility in Water Negligible; 0-1% Partition coefficient: n-octanol/water No data available **Auto-ignition Temperature** No data available

Revision Date: 06-08-2015 Product Code: FC7510

**Decomposition Temperature:** No data available **Viscosity** 89 - 109 KU

Volatiles, % by volume 3.41
Volatiles, % by weight 1.95

Volatile Organic Chemicals (g/L)

(Regulatory, Calculated) 27.92 (Actual, Calculated) 27.92

**Density** 11.83 - 12.03 lbs./Gal

**10. STABILITY AND REACTIVITY** 

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions No data available

Conditions to Avoid

Temperatures above the high flash point of this combustible

material in combination with sparks, open flames, or other

sources of ignition. Contamination.

Incompatible Materials Oxidizing agents

11. TOXICOLOGICAL INFORMATION

Routes of Exposure Inhalation

Skin contact Eye contact

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Inhalation of dusts produced during cutting, grinding or sanding of this

product may cause irritation of the respiratory tract.

Long-Term (Chronic) Health Effects

Carcinogenicity Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic

to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals.

Cancer hazard: Contains Crystalline Silica, which can cause cancer. Risk of

cancer depends on duration and level of exposure to dust generated from

sanding surfaces or spray mists.

**Inhalation** Overexposure may cause lung damage.

**Product Toxicology Data** 

Inhalation Dust/Mist Acute Toxicity Estimate 64.95 mg/L

(ATE)

**Component Toxicology Data** 

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	Oral LD50 Rat 6450 mg/kg	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
		2000 mg/kg	5.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
	mg/kg	10,000 mg/kg	6.82 mg/L
Crystalline Aluminosilicate	Oral LD50 Rat > 5110	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
	mg/kg	2000 mg/kg	3.35 mg/L
Quartz	Oral LD50 Rat > 22,500	Dermal LD50 Rabbit >	Inhalation LC50 (4h) Rat >
	mg/kg	2000 mg/kg	20.00 mg/L

**Carcinogen Information** 

Chemical Name IARC Carcinogen OSHA Carcinogen NTP Carcinogen

Titanium dioxide 2B
Quartz 1 1

Revision Date: 06-08-2015 Product Code: FC7510

### 12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and

No data available

terrestrial, where available)

Mobility in soil No data available

### 13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste

Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

### 14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

**DOT Basic Description:** Paint, Not-Regulated

IATA Air Shipping Name: Paint, Not-Regulated

IMO Shipping Name: Paint, Not-Regulated

Marine Pollutant: N

### 15. REGULATORY INFORMATION

**TSCA Status** 

All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

### **Regulated Components**

SARA EHS Chemicals

<u>CAS #</u> %

### **CERCLA**

Not applicable

Not applicable

### **SARA 313**

Not applicable

### SARA 311/312

Health (Acute): Y
Health (chronic): Y
Fire (Flammable): N
Pressure: N
Reactivity: N

### U. S. State Regulations:

#### California Prop 65 Chemicals

Cancer	<u>CAS #</u>	<u>%</u>
Titanium dioxide	13463-67-7	3 - 7
Crystalline Silica	14808-60-7	0.1 - 1
Cumene	98-82-8	0.001- 0.01
Benzene	71-43-2	< 10 ppm
Reproductive		
Benzene	71-43-2	< 10 ppm

Revision Date: 06-08-2015 Product Code: FC7510

**Canadian Regulations**:

**CEPA DSL:** The components of this product ARE listed on the Canadian Domestic Substances

List.

WHMIS Hazard Class: D2A

### **16. OTHER INFORMATION**

Revision Date Disclaimer

06-08-2015

This SDS has been prepared in accordance with the OSHA Hazard Communication

Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This

information is furnished without warranty, expressed or implied.