

Safety Data Sheet

Revision Date: 01-15-2016
Product Code: FC7530

1. IDENTIFICATION

Product Name	FC ALIPHATIC URETHANE TOP COAT GRAY
Product Code	FC7530
Document ID	GFC7530
Revision Number	1
Prior Version Date	None
Intended Use	Industrial Maintenance Floor TopCoat Urethane
Restrictions On Use	For Industrial Use Only
Chemical Family	Urethane Floor Coating
Chemical Manufacturer / Importer	NEOGARD® - a Division of JONES-BLAIR® Company, LLC 2728 Empire Central Dallas, TX 75235 1-214-353-1600
Emergency Telephone Number:	ChemTrec Center 1-800-424-9300 International: 703-527-3887

2. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

Hazard Pictograms



GHS Classification

Respiratory Sensitisation Category 1A
Skin Sensitisation Category 1B
Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2
Carcinogenicity Category 2
Acute Toxicity - Inhalation Dust / Mist Category 3
Acute Toxicity - Inhalation Vapour Category 3
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word

Danger

Hazard Statements

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary Statements

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, fume, mist, vapours or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection and face protection. Use personal protective equipment as required. In case of inadequate ventilation wear respiratory protection.

Safety Data Sheet

Revision Date: 01-15-2016

Product Code: FC7530

Response	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. Call a POISON CENTER or physician if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms: Call a POISON CENTER or physician. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards Not Otherwise Classified (HNOC)	Not applicable

Additional Information

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Component</u>	<u>CAS #</u>	<u>%</u>
Homopolymer of Isophorone Diisocyanate	53880-05-0	50 - 70
Titanium dioxide	13463-67-7	5 - 10
ISOPHORONE DIISOCYANATE	4098-71-9	1 - 5
Molecular sieves, 5A	69912-79-4	1 - 5
(d)-Limonene	5989-27-5	0.1 - 1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 1
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	0.1 - 1
Carbon black	1333-86-4	0.1 - 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If breathing difficulty persists or occurs later, consult a physician and have MSDS available.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Thoroughly wash or discard clothing and shoes before reuse.
Ingestion	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS.
Most Important Acute Symptoms and Effects	Not Available
Most Important Delayed Symptoms and Effects	Not Available
Special treatment needed:	No additional first aid information available

Safety Data Sheet

Revision Date: 01-15-2016
Product Code: FC7530

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
Unsuitable Extinguishing Media	No data available
Fire and/or Explosion Hazards	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Hazardous Combustion Products	Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Hydrogen cyanide, Isocyanic Acid
Special Protective Equipment and Precautions for Fire-Fighters	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures	Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. See MSDS sections III, XIII and XV for disposal considerations.
Methods and Material for Containment and Cleaning Up	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal.

7. HANDLING AND STORAGE

Precautions for Safe Handling	Overexposure may be harmful. As with all chemicals, good industrial hygiene practices should be followed when handling this material.
Conditions for Safe Storage	Store in a cool dry place. Keep container(s) closed.
Materials to Avoid/Chemical Incompatibility	Moisture, Amines, Alcohols, Caustics (bases, alkalis), Oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits

<u>Chemical Component</u>	<u>OSHA PEL</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH STEL</u>
Titanium dioxide	15 mg/m ³ TWA (total dust)	10 mg/m ³ TWA	
Isophorone Diisocyanate		0.005 ppm (TWA)	
Carbon black	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	

Appropriate Engineering Controls Respiratory Protection

Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure. General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use. For poorly ventilated areas or during spray application use NIOSH approved supplied air respirator unless air monitoring demonstrates vapor/mist levels below applicable limits. When monomeric isocyanate concentrations are below 0.05 ppm (10 times the 8 hour TWA exposure limit), an appropriate combination organic vapor and particulate respirator (NIOSH approved) may be appropriate. An end-of-service-life Indicator (ESLI) or a change schedule is mandatory.

Eye Protection

Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash

Safety Data Sheet

Revision Date: 01-15-2016
Product Code: FC7530

Skin Protection	station available. Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact.
General Hygiene Conditions	As with all chemicals, good industrial hygiene practices should be followed when handling this material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical State	Liquid
Color	Grey
Odor	No data available
Odor Threshold	No data available
pH	No data available
Melting Point/Freezing Point (°F/°C)	No data available / No data available
Initial Boiling Point and Boiling Range	
Low (°F)	No data available
Flash Point (°F/°C)	205 / 96
Flammability (solid, gas)	No data available
Upper Flammable/Explosive Limit	No data available
Lower Flammable/Explosive Limit	0.7
Vapor Density	No data available
Relative Density	1.112
Solubility in Water	Reacts slowly with water.
Partition coefficient: n-octanol/water	No data available
Auto-ignition Temperature	No data available
Decomposition Temperature:	No data available
Viscosity	3,300 - 4,800 CPS
Volatiles, % by volume	5.17
Volatiles, % by weight	3.69
Volatile Organic Chemicals (g/L)	
(Regulatory, Calculated)	40.98
(Actual, Calculated)	40.98
Density	9.18 - 9.38 lbs./Gal

10. STABILITY AND REACTIVITY

Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	No data available
Conditions to Avoid	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Contamination.
Incompatible Materials	Moisture, Amines, Alcohols, Caustics (bases, alkalis), Oxidizing agents
Hazardous Decomposition Products	Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Hydrogen cyanide, Isocyanic Acid

11. TOXICOLOGICAL INFORMATION

Routes of Exposure	Inhalation Skin contact Eye contact
---------------------------	---

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Harmful if inhaled. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Irritating to the nose, throat, and respiratory tract. Sensitizer! Avoid exposure. If
------------------------------	---

Safety Data Sheet

Revision Date: 01-15-2016

Product Code: FC7530

sensitized, exposure below the published exposure limits (e.g. TLV or PEL) can result in respiratory irritation, shortness of breath and difficulty breathing. These asthma-type symptoms may develop immediately or be delayed up to several hours.

Skin Contact

Causes irritation with symptoms of reddening, itching and swelling. Sensitizer. Avoid exposure. If sensitized, repeated exposures will result in irritation, reddening, and rashes even for very low exposures.

Eye Contact

May cause allergic skin reaction. Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.

Ingestion Irritation

Irritating to mouth, throat, and stomach. Can cause abdominal discomfort.

Long-Term (Chronic) Health Effects
Carcinogenicity

Contains Titanium Dioxide which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence with respect to humans and sufficient evidence in experimental animals. Possible cancer hazard. Contains carbon black which may cause cancer based on animal data. (Risk of cancer depends on duration and level of exposure.)

Inhalation

Isocyanate vapors or mist at concentrations above the TLV can irritate the mucous membranes in the respiratory tract causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. Exposure well above the TLV may lead to generally reversible bronchitis, bronchial spasm and pulmonary edema. Repeated overexposure causes sensitization in some individuals resulting in asthma-like symptoms on subsequent exposures below the TLV. Persons with preexisting bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as an asthma attack.

Skin Contact

Prolonged contact may cause an allergic skin reaction.

Product Toxicology Data

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Homopolymer of Isophorone Diisocyanate	Oral LD50 Rat > 14,000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Titanium dioxide	Oral LD50 Rat > 25,000 mg/kg	Dermal LD50 Rabbit > 10,000 mg/kg	Inhalation LC50 (4h) Rat > 6.82 mg/L
Isophorone Diisocyanate	Oral LD50 Rat 5490 mg/kg	Dermal LD50 Rabbit 4780 mg/kg	Inhalation LC50 (4h) Rat 0.03 mg/L
Molecular sieves, 5A	Oral LD50 Rat > 2000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	Inhalation LC50 (4h) Rat > 20.00 mg/L
Carbon black	Oral LD50 Rat > 8000 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	

Carcinogen Information

Chemical Name	IARC Carcinogen	OSHA Carcinogen	NTP Carcinogen
Titanium dioxide	2B		
Carbon black	2B		

12. ECOLOGICAL INFORMATION

Ecotoxicity (aquatic and terrestrial, where available) No data available

Safety Data Sheet

Revision Date: 01-15-2016
Product Code: FC7530

Mobility in soil No data available

13. DISPOSAL CONSIDERATIONS

Safe Handling of Waste Refer to other sections of this SDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint, Not-Regulated

Marine Pollutant: N

15. REGULATORY INFORMATION

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

Regulated Components

SARA EHS Chemicals

	<u>CAS #</u>	<u>%</u>
Isophorone diisocyanate	4098-71-9	1 - 5

CERCLA

Not applicable

SARA 313

Isophorone diisocyanate	4098-71-9	1 - 5
-------------------------	-----------	-------

SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	N
Pressure:	N
Reactivity:	Y

U. S. State Regulations:

California Prop 65 Chemicals

Cancer

	<u>CAS #</u>	<u>%</u>
Titanium dioxide	13463-67-7	5 - 10
Carbon Black	1333-86-4	0.1 - 1
Ethyl Benzene	100-41-4	0.01 - 0.1
Benzene	71-43-2	< 1 ppm

Reproductive

Toluene	108-88-3	0.001- 0.01
Benzene	71-43-2	< 1 ppm

Canadian Regulations:

CEPA DSL:

The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class:

D2A

Safety Data Sheet

Revision Date: 01-15-2016
Product Code: FC7530

16. OTHER INFORMATION

Revision Date 01-15-2016

Disclaimer This SDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.