



TECHNICAL DATA SHEET

Paraseal® Permanent Seam Tape™

Paraseal Accessory

PRODUCT DESCRIPTION

Paraseal® Permanent Seam Tape™ is a 60-mil thick rubberized asphalt membrane laminated to a polyethylene reinforcing film. A removable release paper protects the adhesive membrane face until removed during installation.

BASIC USES

Permanent Seam Tape is used primarily for sealing the seams of Paraseal and Deckseal applications when flood testing is desired. It is used on all seams of Paraseal Saltwater Grade applications and with Paraseal LG when installed for vaporproofing. The inherent adhesive and waterproofing properties of the rubberized-asphalt membrane effectively seams the HDPE liner on Paraseal products to render the bentonite a secondary back up.

AVAILABILITY

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For distributor locations, visit www.tremcosealants.com.

PACKAGING

4" x 75' long rolls (22 M); 6 rolls/case

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

SEAMTAPEDS/1122

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com