



SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaTop® 111/121/122/123 Plus** PART A REVISION DATE: February 10th, 2015

USAGE: POLYMER-MODIFIED REPAIR MORTAR

MANUFACTURER/SUPPLIER: Sika CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9EMERGENCY TELEPHONE NUMBER: **CANUTEC (collect) (613) 996-6666**TDG CLASSIFICATION: Not Regulated
UN NUMBER: Not Established
Packaging Group: Not ApplicableWHMIS Classification: Not Regulated
Class: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
None					

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Liquid
Appearance and Odor: Green liquid, acrylic odor
Odor Threshold: Not Established
Evaporation Rate: < 1 (water)
Vapor Density: < 1 (water)
Vapor Pressure: 17 mm (20°C)Boiling Point: 100°C
Freezing Point: 0°C
Density: 1,02 g/ml
Water Solubility: Yes
pH: 8 - 10
% volatility: 70 - 80
Water/Oil Distribution: Not Established

PRODUCT: **SikaTop® 111/121/122/123 Plus**

PART A

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No

If Yes, under what conditions:

Extinguishing methods: Foam, dry chemical product, CO₂, water hose.

Special Methods: Firefighters must wear their usual protection equipment and respiratory equipment. The water hose could be used to cool down the containers and to dissipate the vapors over the spill.

TDG Flammability Class: Not Regulated
Flammable upper limits (% vol.): Not Applicable
Flammable lower limits (% vol.): Not Applicable
Flash Point (method used): Not Applicable
Auto-ignition temperature: Not Established
Dangerous Combustion Products: Carbon oxides, acrylic monomer.

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes

If not, under what conditions: Excessive heat can degrade the resin.

Incompatibility with other material: No

If Yes, which ones:

Dangerous decomposition products: Carbon oxides, acrylic monomer.

Polymerization Risks: No

PRODUCT: **SikaTop® 111/121/122/123 Plus** PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritation.

Carcinogenicity: Not Established

Skin: May cause skin irritation.

Toxic effects
on reproduction: Not Established

Inhalation: May cause irritation to the lungs.

Teratogenicity: Not Established

Ingestion: May cause irritation to the gastro-
intestinal system.

Mutagenicity: Not Established

Product with synergistic
effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.

PRODUCT: **SikaTop® 111/121/122/123 Plus**

PART A

SECTION VII: PREVENTIVE MEASURES**PERSONAL PROTECTIVE EQUIPMENT**

Gloves: Chemical products resistant gloves.

Respiratory equipment: Not necessary.

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Rubber Apron

Other: No

OTHERS

Ventilation: Sufficient ventilation required.

Procedure in case of leaks: Absorb with sand and other absorbent material

Handling and Equipment methods: Avoid skin, eye and clothing contact.

Warehouse Requirements: Keep all containers closed in a cool, dry area. Protect from freezing.

Special Shipping Instructions: Protect from freezing.

Waste Disposal: Dispose of sand and water according to municipal, provincial and federal laws on chemical waste.

PRODUCT: **SikaTop® 111/121/122/123 Plus** PART A**SECTION VIII: FIRST AID**

Skin: Remove and clean all contaminated clothing.
Wash with plenty of soap and water the exposed areas.
Consult a physician if necessary.

Eyes: Clean with water for at least 15 minutes.
Consult a physician if necessary.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if needed.

Ingestion: Do not induce vomiting. Drink plenty of water.
Do not give anything by mouth to an unconscious person.
Consult a physician if need.

SECTION IX: PREPARATION INFORMATION

Prepared By: The Laboratory, Research and Development Department of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.



SECTION I: PRODUCT INFORMATION

PRODUCT: **SikaTop® 111 Plus** PART B REVISION DATE: February 1st, 2015

USAGE: SELF LEVELING (POLYMER MODIFIED) REPAIR MORTAR

MANUFACTURER/SUPPLIER: Sika CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not Regulated WHMIS Classification: D2A, E
UN NUMBER: Not Established CLASS: Not Applicable
Packaging Group: Not Applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
SILICA SAND	40-70	ACGIH *0.025 mg/m ³	14808-60-7	Not Available	Not Available
PORTLAND CEMENT	30-60	** 10mg/m ³	65997-15-1	Not Available	Not Available
* Total	dust				
** Breathable	dust				

SECTION III: PHYSICAL CHARACTERISTICS

Physical State: Powder
Appearance and Odor: Grey powder, no odor

Odor Threshold: Not Applicable
Evaporation Rate: Not Applicable
Vapor Density: Not Applicable
Vapor Pressure: Not Applicable

Boiling Point: Not Applicable
Freezing Point: Not Applicable
Density: 2.8 g/ml
Water Solubility: < 1 %
pH: Not Established
% volatility: 0
Water/Oil Distribution: Not Established

PRODUCT: **SikaTop® 111 Plus**

PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No

If Yes, under what conditions:

Extinguishing methods: Not applicable.

Special Methods: None.

TDG Flammability Class: Not applicable.

Flammable upper limits (% vol.): Not applicable.

Flammable lower limits (% vol.): Not applicable.

Flash Point (method used): Not applicable.

Auto-ignition temperature: Not applicable.

Dangerous Combustion Products: Not applicable.

Protect from mechanical impact: No

Protect from static discharge: No

SECTION V: REACTIVITY

Chemical stability: Yes

If not, under what conditions:

Dangerous decomposition products: Calcium hydroxide at water contact.

Incompatibility with other material: Yes

If Yes, which ones: Water.

Polymerization Risks: No

PRODUCT: **SikaTop® 111 Plus**

PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause irritation, burns and damages to the eyes. May cause cornea inflammation.

Skin: May cause irritation, burns and allergic reactions. The cement can burn the skin without great heat sensation.

Inhalation: May cause irritation to the respiratory system, inflammation of the nose tissues. A regular exposure to the quartz silica may cause changes to the lungs' fibers and lead to silicosis.

Ingestion: May cause irritation to the throat.

Carcinogenicity: NTP: no, OSHA: no, IARC: yes According to the IARC the quartz silica is a probable cause of cancer.

Toxic effects on reproduction: Not established

Teratogenicity: Not established

Mutagenicity: Not established

Product with synergistic effects: Unknown

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.

PRODUCT: **SikaTop® 111 Plus**

PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Ordinary, avoid direct skin contact with cement.

Respiratory equipment: NIOSH approved mask for dust, when the permissible exposure limit might be exceeded

Eyes: Safety glasses

Shoes: Ordinary

Clothing: Ordinary

Other: No

OTHERS

Ventilation: Sufficient ventilation required to control the dust.

Procedure in case of leaks: Try to recycle if the product is not contaminated. Protect yourself from the dust. Pick-up the spills with a vacuum in order to prevent dust spread.

Handling and Equipment methods: Avoid dust exposure

Warehouse Requirements: Keep all containers closed in a cool, dry area.

Special Shipping Instructions: Protect from humidity.

Waste Disposal: Harden with water and dispose like domestic garbage.

PRODUCT: **SikaTop® 111 Plus**

PART B

SECTION VIII: FIRST AID

Skin: Wash with plenty of soap and water the exposed areas.
Consult a physician if irritation persists.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
See a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.

AQ 191 A

Date: 2012/02/01

App: S.G.