

Printing date 07/30/2019

Reviewed on 07/30/2019

1 Identification

· Product identifier: 2K-PUR COMP A, 327-47-025 (A), 327-47-055 (A), 327-47-105 (A), 2K A MIX

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

· Item number(s): 2K-PUR COMP A, 327-47-025 (A), 327-47-055 (A), 327-47-105 (A), 2K A MIX

· SDS Number: 9

· UPC bar code(s): 12205 5, 12200 0, 12235 2

· Application of the substance / the mixture ROOF COATING

Manufacturer/Supplier:

USA ADDRESS:

KEMPER SYSTEM AMERICA, INC. 1200 NORTH AMERICA DR, WEST SENECA, NY 14224 PH (716) 558-2971

CANADIAN ADDRESS:

KEMPER SYSTEM CANADA 6345 NETHERHART ROAD MISSISSAUGA, ON L5T 1B8 PH (905) 624-5463 FAX (905) 624-2840

· Information department:

Tel: (716) 558-2971 ext. 228 www.kempersystem.net

· Emergency telephone number:

ChemTrec (800) 424-9300 / 1-(703)-741-5970

Canada only: CANUTEC (Call collect) (613) 996-6666

2 Hazard(s) identification

· Classification of the substance or mixture:

This product is not classified as hazardous according to the Globally Harmonized System (GHS).

- Label elements
- · GHS label elements Not Available
- · Signal word: Not Available
- · Hazard statements: Not Available
- · NFPA ratings (scale 0 4):



Health = 1 Fire = 1 Reactivity = 0

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
21645-51-2	aluminium hydroxide	10-30% w/w *
13463-67-7	Titanium Dioxide	1-5% w/w *
		(Contd. on page 2)

- CA

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

* Actual concentration ranges are withheld as a trade secret.

(Contd. of page 1)

4 First-aid measures

- · General information: No special measures required.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Call a poison center/doctor if you feel unwell. Rinse mouth.
- Most important symptoms and effects, both acute and delayed:

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-fighting measures

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures: Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Reference to other sections:

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling: No special measures required.
- · Information about protection against explosions and fires: No special measures required.
- Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 3)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

	(Contd. of page 2)		
· Components	Components with limit values that require monitoring at the workplace:		
21645-51-2 a	21645-51-2 aluminium hydroxide		
EL (Canada)	Long-term value: 10 mg/m³		
REL (USA)	Long-term value: 2 mg/m³ as Al		
TLV (USA)	Long-term value: 1* mg/m³ as Al;*as respirable fraction		
13463-67-7 T	itanium Dioxide		
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction; IARC 2B		
EV (Canada)	Long-term value: 10 mg/m³ total dust		
PEL (USA)	Long-term value: 15* mg/m³ *total dust		
REL (USA)	See Pocket Guide App. A		
TLV (USA)	Long-term value: 10 mg/m³ withdrawn from NIC		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

- · Breathing equipment: Not required.
- Protection of hands:
- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
- Material of gloves:

Protective gloves not normally required. People with sensitive skin may prefer to wear water-proof gloves, such as rubber or neoprene, to avoid skin contact.

• Eye protection: Goggles recommended during refilling.

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not determined.
Flash point:	>100 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	>450 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

		(Contd. of pag
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C:	1 hPa	
Density at 20 °C:	1.246 g/cm³	
Relative density:	Not determined.	
· Vapor density:	Not determined.	
· Evaporation rate:	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
•	Not applicable.	
Kinematic:	Not determined.	
	Not applicable.	
· Solvent content:		
VOC content:	6 g/l	
· Other information	No further relevant information available.	

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects: Not available
- · Acute toxicity
- Specific symptoms in biological assay: No further relevant information available.
- Primary irritant effect
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product is not subject to classification according to internally approved calculation methods for preparations:

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

1318-02-1 Zeolite powder 3 A

3

(Contd. on page 5)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

		(Contd. of page 4)
13463-67-7	Titanium Dioxide	2B
60676-86-0	Silica, fused	3
· NTP (Nation	nal Toxicology Program)	
None of the	ingredients is listed.	

12 Ecological information

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- Behavior in environmental systems
- Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- Additional ecological information
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Smaller quantities can be disposed of with household waste.
- · Uncleaned packagings
- Recommendation:

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

14 Transport information	
· <u>UN-Number</u> · DOT, TDG, ADN, IMDG, IATA	Not regulated
 UN proper shipping name DOT, TDG, ADN, IMDG, IATA 	Not regulated
· Transport hazard class(es)	
· DOT, TDG, ADN, IMDG, IATA · Class	Not regulated
· <u>Packing group</u> · DOT, TDG, IMDG, IATA	Not regulated
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user:	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code:	<u>II of</u> Not applicable.

(Contd. on page 6)

Printing date 07/30/2019 Reviewed on 07/30/2019

<u>Trade name:</u> KEMPEROL® 2K-PUR Waterproofing Component A

(Contd. of page 5)

· <u>UN "Model Regulation":</u> Not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed or exempted

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Canadian substance listings
- · Canadian Domestic Substances List (DSL/NDSL):

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%):

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%):

8001-79-4 Castor oil

- GHS label elements Not Available
- · Hazard pictograms Not Available
- Signal word Not Available
- · Hazard statements Not Available

16 Other information

This SDS format meets ANSI Z400.1-2010, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2015 and ISO 14001:2015 registered company.

· Department issuing SDS: Product safety department

(Contd. on page 7)

Reviewed on 07/30/2019 Printing date 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component A

(Contd. of page 6)

· Contact: Stephen Nowicki

Date of the latest revision of the safety data sheet 07/30/2019 / 9

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)

VOC: Volatile Organic Compounds (USA, EU)



Printing date 07/30/2019

Reviewed on 07/30/2019

1 Identification

Product identifier: 2K-PUR COMP B, 327-47-025 (B), 327-47-055 (B), 327-47-105 (B), 2K COMP B

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

· Item number(s): 2K-PUR COMP B, 327-47-025 (B), 327-47-055 (B), 327-47-105 (B), 2K COMP B

· SDS Number: 11

· UPC bar code(s): 12205 5, 12200 0, 12235 2

· Application of the substance / the mixture ROOF COATING

Manufacturer/Supplier:

USA ADDRESS:

KEMPER SYSTEM AMERICA, INC. 1200 NORTH AMERICA DR, WEST SENECA, NY 14224 PH (716) 558-2971

CANADIAN ADDRESS:

KEMPER SYSTEM CANADA 6345 NETHERHART ROAD MISSISSAUGA, ON L5T 1B8 PH (905) 624-5463 FAX (905) 624-2840

· Information department:

Tel: (716) 558-2971 ext. 228 www.kempersystem.net

· Emergency telephone number:

ChemTrec (800) 424-9300 / 1-(703)-741-5970

Canada only: CANUTEC (Call collect) (613) 996-6666

2 Hazard(s) identification

· Classification of the substance or mixture:



GHS08 Health hazard

Respiratory Sensitizer - Category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific Target Organ Toxicity - Repeated Exposure H373 May cause damage to the respiratory - Category 2

system through prolonged or repeated exposure.



Acute Toxicity (Inhalation) - Category 4 H332 Harmful if inhaled. Skin Irritation - Category 2 H315 Causes skin irritation.

Skin Sensitizer - Category 1 H317 May cause an allergic skin reaction. Specific Target Organ Toxicity - Single Exposure - H335 May cause respiratory irritation.

Category 3

H320 Causes eye irritation.

Eye Irritation - Category 2B

· Additional information:

At temperatures up to 77°F (25°C), this product does not emit sufficient vapors to pose a respiratory hazard when used as directed. Above this temperature, concentrations may become hazardous in

(Contd. on page 2)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 1)

enclosed spaces. Ventilation using open windows, fans, or other means of creating airflow is typically a sufficient engineering control to maintain adequate ventilation at working temperatures.

· Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Signal word: Danger

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate,isomeres and homologues

methylenediphenyl diisocyanate

· Hazard statements:

H332 Harmful if inhaled.

H315+H320 Causes skin and eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H373 May cause damage to the respiratory system through prolonged or repeated exposure.

Precautionary statements:

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302+P352 If on skin: Wash with plenty of soap and water. P304+P312 IF INHALED: Call a doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a doctor.
Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· NFPA ratings (scale 0 - 4):



3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

		(Contd. of page 2)
Dangerous components:		
101-68-8	4,4'-methylenediphenyl diisocyanate	30-60% w/w *
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	30-60% w/w *
26447-40-5	methylenediphenyl diisocyanate	5% w/w
* Actual concentration ranges are withheld as a trade secret.		

4 First-aid measures

- · General information: Symptoms of poisoning may even occur after several hours.
- · After inhalation:

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor if you feel unwell or are experiencing respiratory symptoms.

· After skin contact:

Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

· After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

- · After swallowing: If swallowed, do not induce vomiting. Get medical attention right away.
- · Most important symptoms and effects, both acute and delayed:

No further relevant information available.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-fighting measures

- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture: No further relevant information available.
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures: See below:
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 3)

- · Information about protection against explosions and fires: No special measures required.
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s): No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.		
Components with limit values that require monitoring at the workplace:		
101-68-8 4,4'	-methylenediphenyl diisocyanate	
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S(R)	
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm	
PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm	
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min	
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm	
9016-87-9 di	phenylmethanediisocyanate,isomeres and homologues	
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm S	
26447-40-5 n	nethylenediphenyl diisocyanate	
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm S	

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves:

Nitrile rubber, NBR

Natural rubber, NR

(Contd. on page 5)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

· Eye protection:



Tightly sealed goggles

(Contd. of page 4)

Physical and chemical prope	erties
Form: Color: Odor: Odor threshold:	Fluid According to product specification Characteristic Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. >350 °C
Flash point:	>200 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	400 °C
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits Lower: Upper:	0.4 Vol % 0.0 Vol %
Vapor pressure:	Not determined. Not applicable.
Density at 20 °C: Relative density: Vapor density: Evaporation rate:	1.24 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity: Dynamic:	Not determined. Not applicable.
Kinematic:	Not determined. Not applicable.
Solvent content: VOC content:	6 g/l

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 5)

Other information

No further relevant information available.

10 Stability and reactivity

- Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects:
- Acute toxicity
- · LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

- Specific symptoms in biological assay: No further relevant information available.
- · Primary irritant effect
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
101-68-8 4,4'-methylenediphenyl diisocyanate	3	
9016-87-9 diphenylmethanediisocyanate,isomeres and homologues	3	
NTP (National Toxicology Program)		

12 Ecological information

None of the ingredients is listed.

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.

(Contd. on page 7)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 6)

- · Additional ecological information
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Other adverse effects: No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings
- · Recommendation:

Place in a sealed container and label as waste. Place in a safe area, and comply with all federal, state, provincial and local regulations for disposal.

14 Transport information	
· <u>UN-Number</u> · DOT, TDG, ADN, IMDG, IATA	Not regulated
· UN proper shipping name · DOT, TDG, ADN, IMDG, IATA	Not regulated
· Transport hazard class(es)	
· DOT, TDG, ADN, IMDG, IATA · Class	Not regulated
· <u>Packing group</u> · DOT, TDG, IMDG, IATA	Not regulated
· Environmental hazards: · Marine pollutant:	No
Special precautions for user:	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code:	II of Not applicable.
UN "Model Regulation":	Not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

(Contd. on page 8)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 7)

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

· TSCA (Toxic Substances Control Act):

All ingredients are listed or exempted

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Canadian substance listings

· Canadian Domestic Substances List (DSL/NDSL):

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%):

101-68-8 4,4'-methylenediphenyl diisocyanate

· Canadian Ingredient Disclosure list (limit 1%):

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocvanate.isomeres and homologues

methylenediphenyl diisocyanate

Hazard statements

H332 Harmful if inhaled.

H315+H320 Causes skin and eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

H373 May cause damage to the respiratory system through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

P302+P352 If on skin: Wash with plenty of soap and water.

(Contd. on page 9)

Printing date 07/30/2019 Reviewed on 07/30/2019

Trade name: KEMPEROL® 2K-PUR Waterproofing Component B

(Contd. of page 8) P304+P312 IF INHALED: Call a doctor if you feel unwell. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/attention if you feel unwell. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a doctor. P342+P311 Take off contaminated clothing and wash it before reuse. P362+P364 P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

16 Other information

This SDS format meets ANSI Z400.1-2010, OSHA 1910.1200 and WHMIS requirements. Kemper System America, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Kemper System America, Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Kemper System America, Inc is an ISO 9001:2015 and ISO 14001:2015 registered company.

- · Department issuing SDS: Product safety department
- · Contact: Stephen Nowicki
- Date of the latest revision of the safety data sheet 07/30/2019 / 4
- Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose 50 percent

LD50: Lethal dose, 50 percent

* Data compared to the previous version altered.

- CA