

## **PRODUCT DESCRIPTION**

Dymonic 100 is a high-performance, high-movement, single-component, medium-modulus, low-VOC, UV-stable, non-sag polyurethane sealant.

ALMOND	IVORY	ALUMINUM STONE	LIGHT BRONZE
ANODIZED ALUMINUM	LIMESTONE	BEIGE	NATURAL CLAY
BLACK	OFF WHITE	BRONZE	PRECAST WHITE
BUFF	REDWOOD TAN	DARK BRONZE	SANDALWOOD
GRAY	STONE	GRAY STONE	WHITE
HARTFORD GREEN			

This guide only offers a general representation of our color offering. Colors viewed on a computer screen and then printed will vary and will never be an exact representation of the actual pigment. When matching is critical, please refer to our color card or sample color strips.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.



Tremco® and Dymonic® are registered trademarks of Tremco Incorporated. Willseal is a registered trademark of Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.