

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

1 Identification

- **Product identifier**
- **Trade name:** Pro-Poxy™ 300 Fast - Part A
- **Article number:** 140204A
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Muta. 2 H341 Suspected of causing genetic defects.
Carc. 2 H351 Suspected of causing cancer.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Warning
- **Hazard-determining components of labeling:**
2,3-epoxypropyl o-tolyl ether
titanium dioxide
- **Hazard statements**
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
Suspected of causing cancer.
Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 1)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
PHYSICAL HAZARD	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
25085-99-8	Diglycidyl ether of bisphenol A homopolymer	≥10-<90%
2210-79-9	2,3-epoxypropyl o-tolyl ether	≥2.5-<4%
471-34-1	calcium carbonate	<4.0%
67762-90-7	Hydrophobic silica	<3.25%
13463-67-7	titanium dioxide	≥0.1-<1.6%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
In the event of persistent symptoms receive medical treatment.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Seek immediate medical advice.
Seek medical treatment.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** Store in a cool dry location.
- **Information about storage in one common storage facility:** Store away from incompatible materials.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 3)

471-34-1 calcium carbonate

PEL Long-term value: 15* 5** mg/m³
*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³
*total dust **respirable fraction

TLV TLV withdrawn

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Mild

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** >93 °C (>199.4 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 4)

Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.2 g/cm ³ (10.014 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	1,000,000 mPas
Kinematic:	Not determined.
· Solvent content:	
Solids content:	100.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

25085-99-8 Diglycidyl ether of bisphenol A homopolymer

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong irritant with the danger of severe eye injury.
Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 5)

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc	3
13463-67-7	titanium dioxide	2B
7631-86-9	silicon dioxide, chemically prepared	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

· **UN-Number**

· **DOT, ADR, ADN, IATA**

· **IMDG**

Not Regulated

UN3082

(Contd. on page 7)

Safety Data Sheet



acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 6)

<ul style="list-style-type: none"> · UN proper shipping name · DOT, ADR, ADN, IATA · IMDG 	<p style="text-align: center;">Not Regulated</p> <p style="text-align: center;">ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin), MARINE POLLUTANT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADR, ADN, IATA · Class 	Not Regulated
<ul style="list-style-type: none"> · IMDG <div style="display: flex; justify-content: space-around; align-items: center;">   </div> <ul style="list-style-type: none"> · Class · Label 	<p style="text-align: center;">9 Miscellaneous dangerous substances and articles</p> <p style="text-align: center;">9</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p style="text-align: center;">No</p> <p style="text-align: center;">Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · Special precautions for user · EMS Number: · Stowage Category 	<p style="text-align: center;">F-A,S-F</p> <p style="text-align: center;">A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Remarks: 	Not Regulated for Transport.
<ul style="list-style-type: none"> · ADR · Remarks: · U.S. Domestic Ground Shipments: · U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments: · Emergency Response Guide (ERG) Number: 	<p style="text-align: center;">Not Regulated for Transport.</p> <p style="text-align: center;">Same as listed for Standard Shipments above.</p> <p style="text-align: center;">Same as listed for Standard Shipments above.</p> <p style="text-align: center;">Not determine</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p style="text-align: center;">5L</p> <p style="text-align: center;">Code: E1</p> <p style="text-align: center;">Maximum net quantity per inner packaging: 30 ml</p> <p style="text-align: center;">Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	Not Regulated

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 7)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

25085-99-8	Diglycidyl ether of bisphenol A homopolymer	ACTIVE
2210-79-9	2,3-epoxypropyl o-tolyl ether	ACTIVE
471-34-1	calcium carbonate	ACTIVE
67762-90-7	Hydrophobic silica	ACTIVE
14807-96-6	Talc	ACTIVE
13463-67-7	titanium dioxide	ACTIVE
7631-86-9	silicon dioxide, chemically prepared	ACTIVE
21645-51-2	aluminium hydroxide	ACTIVE
63148-62-9	Siloxanes and Silicones, di-Me	ACTIVE

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc	A4
13463-67-7	titanium dioxide	A4

· **MAK (German Maximum Workplace Concentration)**

14807-96-6	Talc	3B
13463-67-7	titanium dioxide	3A

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part A

(Contd. of page 8)

· Hazard pictograms



GHS07 GHS08

· Signal word *Warning*

· Hazard-determining components of labeling:

2,3-epoxypropyl o-tolyl ether
titanium dioxide

· Hazard statements

Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing genetic defects.
Suspected of causing cancer.
Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves/protective clothing/eye protection/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environmental, Health & Safety Department

· Contact: Environmental, Health & Safety Manager

· Date of preparation / last revision 04/25/2023 / 222

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

1 Identification

- **Product identifier**

- **Trade name:** Pro-Poxy™ 300 Fast - Part B

- **Article number:** 140204B

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Acute Tox. 4 H332 Harmful if inhaled.

Skin Corr. 1C H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

m-phenylenebis(methylamine)

cyclohex-1,2-ylenediamine

- **Hazard statements**

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 1)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 1

Reactivity = 2

· **HMIS-ratings (scale 0 - 4)**

HEALTH	3
FIRE	1
PHYSICAL HAZARD	2

Health = 3

Fire = 1

Reactivity = 2

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

471-34-1	calcium carbonate	<70.0%
104-40-5	nonylphenol	<20.0%
1477-55-0	m-phenylenebis(methylamine)	≥5-<15%
14808-60-7	Quartz (SiO ₂)	≥0.1-<3.75%
546-93-0	Magnesite	<1.2%
694-83-7	cyclohex-1,2-ylenediamine	≥0.1-<0.7%
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	≥0.1-≤0.3%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 2)

- **After swallowing:**
*Drink copious amounts of water and provide fresh air. Immediately call a doctor.
 Seek medical treatment.*
- **Information for doctor:**
Most important symptoms and effects, both acute and delayed No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** *No further relevant information available.*
- **Advice for firefighters**
- **Protective equipment:**
*Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.
 Mouth respiratory protective device.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
*Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.*
- **Methods and material for containment and cleaning up:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Use neutralizing agent.
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.*

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:** *Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool dry location.*
- **Information about storage in one common storage facility:** *Store away from incompatible materials.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Specific end use(s)** *No further relevant information available.*

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

471-34-1 calcium carbonate	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn
1477-55-0 m-phenylenebis(methylamine)	
REL	Ceiling limit value: 0.1 mg/m ³ Skin
TLV	Ceiling limit value: 0.1 mg/m ³ , 0.018 ppm Skin
14808-60-7 Quartz (SiO₂)	
PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction
546-93-0 Magnesite	
PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection: Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Grey
Odor:	Distinctive
Odor threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point: >94 °C (>201.2 °F)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 370 °C (698 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:	1.0 Vol %
Upper:	0.0 Vol %

· Vapor pressure: Not determined.

· Density at 20 °C (68 °F): 1.776 g/cm³ (14.82072 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

· Solvent content:

Solids content: 100.0 %

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 5)

· **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Reacts with acids, alkalis and oxidizing agents.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Nitrogen oxides

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1,040 mg/kg (rat)
------	------	-------------------

Inhalative	LC50/4 h	2.4 mg/l (rat)
------------	----------	----------------

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14808-60-7	Quartz (SiO ₂)	I
------------	----------------------------	---

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
------------	----------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B


(Contd. of page 6)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
*Water hazard class 1 (Self-assessment): slightly hazardous for water
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
*Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
 It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.*
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|--|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="margin-left: 20px;">UN1760</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG · IATA | <p style="margin-left: 20px;"><i>Corrosive liquids, n.o.s. (nonylphenol)</i>
 1760 CORROSIVE LIQUID, N.O.S. (nonylphenol),
 ENVIRONMENTALLY HAZARDOUS
 CORROSIVE LIQUID, N.O.S. (nonylphenol), MARINE
 POLLUTANT
 CORROSIVE LIQUID, N.O.S. (nonylphenol)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <p style="margin-left: 20px;">8 Corrosive substances</p> |
| <div style="text-align: center;">  <p>Corrosive</p> </div> <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">8</p> |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 7)

· **ADR, IATA**

· **Class** 8 Corrosive substances
 · **Label** 8

· **IMDG**

· **Class** 8 Corrosive substances
 · **Label** 8

· **Packing group**
 · **DOT, ADR, IMDG, IATA**

III

· **Environmental hazards:** Product contains environmentally hazardous substances:
 nonylphenol
 · **Marine pollutant:** Yes
 Symbol (fish and tree)

· **Special precautions for user** Warning: Corrosive substances
 · **Danger code (Kemler):** 80
 · **EMS Number:** F-A,S-B
 · **Stowage Category** A
 · **Stowage Code** SW2 Clear of living quarters.

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**
 · **Remarks:** Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).

· **ADR**
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml
 Same as listed for Standard Shipments above.
 · **U.S. Domestic Ground Shipments:**
 · **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.
 · **Emergency Response Guide (ERG) Number:** Not determine

· **IMDG**

· **Limited quantities (LQ)** 5L
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 8)

· UN "Model Regulation":

UN 1760 CORROSIVE LIQUID, N.O.S. (NONYLPHENOL), 8, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

104-40-5	nonylphenol	<20.0%
----------	-------------	--------

· TSCA (Toxic Substances Control Act):

471-34-1	calcium carbonate	ACTIVE
104-40-5	nonylphenol	ACTIVE
1477-55-0	m-phenylenebis(methylamine)	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
546-93-0	Magnesite	ACTIVE
694-83-7	cyclohex-1,2-ylenediamine	ACTIVE
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic	ACTIVE
12227-89-3	Ferric Oxide	ACTIVE
124-09-4	hexamethylenediamine	ACTIVE
156-87-6	3-aminopropan-1-ol	ACTIVE
110-60-1	tetramethylenediamine	ACTIVE
15520-10-2	2-methylpentane-1,5-diamine	ACTIVE
63148-62-9	Siloxanes and Silicones, di-Me	ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)	
14808-60-7 Quartz (SiO ₂)	A2
· MAK (German Maximum Workplace Concentration)	
14808-60-7 Quartz (SiO ₂)	1
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
14808-60-7 Quartz (SiO ₂)	

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

m-phenylenebis(methylamine)

cyclohex-1,2-ylenediamine

· **Hazard statements**

Harmful if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/25/2023 / 287

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 04/25/2023

Reviewed on 04/25/2023

Trade name: Pro-Poxy™ 300 Fast - Part B

(Contd. of page 10)

*CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Acute Tox. 4: Acute toxicity – Category 4**Skin Corr. 1C: Skin corrosion/irritation – Category 1C**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Repr. 2: Reproductive toxicity – Category 2**Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

US