



Last Rev Date: 05/22/2012

**Physical Properties**

<b>Appearance</b> Roll mesh fabric	<b>Maximum VOC</b> 0 g/l	<b>Mesh Size</b> 20X10
<b>Color</b> Yellow	<b>Maximum VOS</b> 0 lbs/gal	<b>Tensile Strength Film (Initial)</b> 75 lbs/in
<b>Flash Point</b> >212°F		

**Description**

**HE183 - REPAIR FABRIC YELLOW FIBERGLASS** is a woven fabric, 20 x 10 mesh, made of yarns of inert, flexible filaments of pure glass. It has a tensil strength of 75 lb/in., stability and durability, is acid and heat resistant, and will not rot or decay.

The special yellow resin coating on the fabric minimizes distortion, and is compatible with asphalt cements and coatings, emulsions, solvent-based and hot-melt types. Since the yellow color is conspicuous if not completely covered, it also aids quality workmanship.

**Usage**

**HE183 - REPAIR FABRIC YELLOW FIBERGLASS** is designed to reinforce **Henry #204 Plastic Roof Cement, #209 Elastomastic, #208 Wet Patch Roof Cement** and **#906 FlashMaster™ Plus Wet or Dry Elastomeric Flashing Cement** and coatings when used in roof repair work, for flashings, and for sealing seams in metal and composition roofs. It is also used in below-grade waterproofing applications, tank lining systems, and for waterproofing planter boxes.

**Application**

Apply roof cement approximately 1/8" thick, or coating approximately 1/16" thick or as specified. Embed product smoothly, without wrinkles or buckles. Top coat the fabric with roof cement or coating of the same thickness as the embedding coat, or as specified, making sure the glass is entirely covered.

**Product Sizes**

6IN X 25FT ROLL (0.5 lb)  
36IN X 150FT ROLL (6.83 lb)

4IN X 150FT ROLL (0.75 lb)

6IN X 150FT ROLL (1.14 lb)

## Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**