

SAFETY DATA SHEET



PECORA DYNATROL II-SL BASE

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 IDENTIFICATION of the SUBSTANCE or PREPARATION

PRODUCT IDENTIFIER/TRADE NAME (AS LABELED)	PECORA DYNATROL II-SL BASE
OTHER MEANS OF IDENTIFICATION	DynaTrol II Part B
RECOMMENDED PRODUCT USE:	DynaTrol II Self-Leveling Base
RESTRICTIONS ON USE:	Other than recommended use

1.2 U.S. COMPANY/UNDERTAKING IDENTIFICATION:

U.S. SUPPLIER/MANUFACTURER'S NAME:	Pecora Corporation
ADDRESS:	165 Wambold Road, Harleysville, PA 19438
EMERGENCY PHONE:	800-424-9300 (CHEMTREC, 24-hours)
BUSINESS PHONE:	215-723-6051 (Mon-Fri, 8 AM-5 PM ET)
PREPARATION DATE:	October 31, 2023
REVISION DATE:	New

This product is sold for commercial use. This SDS has been developed to address safety concerns of those individuals working with bulk quantities of this material, as well as those of potential users of this product in industrial/occupational settings.

2. HAZARD IDENTIFICATION

2.1 GLOBAL HARMONIZATION LABELING AND CLASSIFICATION: Classified in accordance with Global Harmonization Standard under U.S. OSHA Hazard Communication Standard, Canadian WHMIS HPR-GHS 2015.

2.1.1 Classification:

Germ Cell Mutagen Cat. 2, Carcinogen Category 1B, Reproductive Toxicity Category 1B Skin Irritation Category 2; Skin Sensitization Category 1B, Eye Corrosion/Irritation Category 2A, Specific Target Organ Toxicity (Inhalation-Respiratory Irritation) Single Exposure Category 3, Aquatic Chronic Toxicity Category 3

2.1.2 Signal Word: Danger

2.1.3 Hazard Statements:

H341: Suspected of causing genetic effects. H350: May cause cancer. H360FD: May damage fertility. May damage the unborn child. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H412: Harmful to aquatic life with long-lasting effects.

2.1.4 Hazards Not Otherwise Classified (HNOC): Contains multiple trace compounds that may cause adverse effects on the thymus and immune system after chronic exposure. Contains a trace compound that is suspected to be Considered to be a PBT (Persistent, Bioaccumulative and Toxic) in the Environment Compound. Under Assessment as a POP (Persistent Organic Pollutant) Compound.

2.1.5 Physical Hazards Not Otherwise Classified (PHNOC): None known.

2.1.6 Precautionary Statements:

2.1.6.1 Prevention:

P203: Obtain, read and follow all safety instructions before use. P261: Avoid breathing vapors. P264 + P265: Wash hands and other contamination areas thoroughly after handling. Do not touch eyes. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves, clothing, eye protection and face protection.

2.1.6.2 Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P333 + P313: If skin irritation or rash occurs, get medical attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. P337 + P317: If eye irritation persists: get medical help. P304 + P340: If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. P319: Get medical help if you feel unwell. P321: Specific treatment (remove from exposure and treat symptoms).

2.1.6.3 Storage:

P403 + P233 + P405: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

2.1.6.4 Disposal:

P501: Dispose of contents/containers in accordance with all local, regional, national and international regulations.

2.1.7 Hazard Symbols/Pictograms: GHS07, GHS08



2.2 Percent of Unknown Acute Toxicity: This product is a mixture; the following are percentages of unknown acute toxicity, by route of exposure. Oral: < 2% Dermal > 14%, and Inhalation: > 64%

3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical Name	CAS #	W/W%	LABEL ELEMENTS GHS Classification under U.S. OSHA Hazard Communication Standard & Canadian WHMIS (HPR-GHS) 2015 Hazard Statement Codes
Proprietary Prepolymer		40-60	Classification: Not Classified
Proprietary Terephthalate		13.2%	Classification: Not Classified
Calcium Carbonate (Limestone)	1317-65-3	8-15%	Notified Classification: Skin Irritation Cat. 2 Hazard Statements: H315: Causes skin irritation.
Soda Lime Glass	65997-17-3	5-15%	Notified Classification: Carcinogen Cat. 1B Hazard Statements: H350i: May cause cancer by inhalation.
Calcium Oxide	1305-78-8	1-5%	Notified Classification: Skin Irritation Cat. 2, Eye Corrosion/Damage Cat. 1, Specific Target Organ Toxicity (Inhalation-Respiratory Irritation) Single Exposure Cat. 3 Hazard Statements: H315: Causes skin irritation. H318: Causes serious eye damage. H335: May cause respiratory irritation.
Calcium Sulfate Blend		1.5%	Classification: Not Applicable
Xylene	1330-20-7	1-3%	Harmonized Classification: Flammable Liquid Cat. 3, Acute Dermal Toxicity Cat. 4, Acute Inhalation Toxicity Cat. 4, Skin Irritation Cat. 2 Self-Classification: Acute Oral Toxicity Cat. 5, Eye Corrosion-Irritation Cat. 2A Hazard Statements: H226: Flammable liquid and vapor. H312 + H332: Harmful in contact with skin or if inhaled. H315: Causes skin irritation. H303: May be harmful if swallowed. H319: Causes serious eye irritation.
Siloxanes and Silicones		1-3%	U.S. PNOG Hazard: Combustible Dust Hazard
Distillates (Petroleum) Hydrotreated Heavy Paraffinic	64742-65-0	< 1%	Harmonized Classification: Carcinogenic Cat. 1B* Notified Classification: Aspiration Hazard Cat. 1 Hazard Statements: H350: May cause cancer. *H304: May be fatal if swallowed and enters airways.
Titanium Dioxide	13463-67-7	0.3-0.8%	Harmonized Classification: Carcinogen Cat. 2 Hazard Statements: H350i: May cause cancer by inhalation.
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1-0.5%	Notified Classification: Skin Sensitization Cat. 1, Aquatic Acute Toxicity Cat. 1, Aquatic Chronic Toxicity Cat. 1 Hazard Statements: H317: May cause an allergic skin reaction. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long-lasting effects.
Proprietary Acrylonitrile/Methylacrylonitrile Copolymer		0.1-0.5%	Classification: Not Determined
Proprietary Stearate		0.1-0.5%	Classification: Not Applicable
Ethyl Benzene	100-41-4	0.1-0.3%	Harmonized Classification: Flammable Liquid Cat. 2, Acute Inhalation Toxicity Cat. 4, Specific Target Organ Toxicity (Inhalation-Auditory Organs) Repeated Exposure Cat. 2 Notified Classification: Germ Cell Mutagen Cat. 1, Carcinogenic Cat. 1, Acute Oral Toxicity Cat. 3, Aquatic Chronic Toxicity Cat. 3 Hazard Statements: H225: Highly flammable liquid and vapor. H340: May cause genetic effects. H350: May cause cancer. H302 + H332: Harmful if swallowed or inhaled. H372: Causes damages to auditory organ through prolonged or repeated inhalation exposure. H402: Harmful to aquatic life. H413: May cause long-lasting harmful effects to aquatic life.
[3-(2,3-epoxy-propoxy) propyl] Trimethoxysilane	2530-83-8	0.1-0.3%	Notified Classification: Eye Corrosion Damage Cat. 1, Aquatic Chronic Toxicity Cat. 3 Hazard Statements: H318: Causes serious eye damage. H412: Harmful to aquatic life with long-lasting effects.
2-(2H-Benzotriazol-2-yl-4,6-di-tert-pentylphenol	25973-55-1	0.1-0.3%	Notified Classification: Specific Target Organ Toxicity (Oral-Liver, Kidneys) Repeated Exposure Cat. 2 Hazard Statements: H373: May cause damage to the liver and kidneys through prolonged or repeated exposure. Hazards Not Otherwise Classified: Considered to be a PBT (Persistent, Bioaccumulative and Toxic) in the Environment) Compound. Under Assessment as a POP (Persistent Organic Pollutant) Compound
p-Toluene sulfonylisocyanate	4083-64-1	0.1-0.3%	Harmonized Classification: Skin Irritation Cat. 2, Eye Corrosion/Irritation Cat. 2A, Respiratory Sensitization Cat. 1, Specific Target Organ Toxicity (Inhalation-Respiratory Irritation) Single Exposure Cat. 3 Hazard Statements: H315: Causes skin irritation. H319: Causes serious eye irritation. H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335: May cause respiratory irritation.
Methyl 1,2,2,6-pentamethyl-4-piperidyl Sebacate	82919-37-7	0.1-0.3%	Notified Classification: Skin Sensitization Cat. 1, Aquatic Acute Toxicity Cat. 1, Aquatic Chronic Toxicity Cat. 1 Hazard Statements: H317: May cause an allergic skin reaction. H400: Very toxic to aquatic life. H410: Very toxic to aquatic life with long-lasting effects. EU ECHA Properties of Concern: Suspected Persistent in the Environment: The Danish QSAR database contains information indicating that the substance is predicted as non-readily biodegradable.

Note: *Carcinogenic Classification is based upon presence in this compound of DMSO of 3% or more.

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

3. COMPOSITION AND INFORMATION ON INGREDIENTS (Continued)

Chemical Name	CAS #	W/W%	LABEL ELEMENTS GHS Classification under U.S. OSHA Hazard Communication Standard & Canadian WHMIS (HPR-GHS) 2015 Hazard Statement Codes
Dibutyltin Dilaurate	77-58-7	0.1-0.3%	Harmonized Classification: Germ Cell Mutagen Cat. 2, Reproductive Toxicity Cat. 1B, Germ Cell Mutagen Cat. 2, Specific Target Organ Toxicity (Immune System) Repeated Exposure Cat. 1 Notified Classification: Eye Corrosion-Irritation Cat. 2A, Skin Sensitization Cat. 1, Specific Target Organ Toxicity (Immune System) Single Exposure Cat. 1, Aquatic Acute Toxicity Cat. 1 Hazard Statements: H341: Suspected of causing genetic effects. H360FD: May damage fertility. May damage the unborn child. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H371: May cause damage to immune system and thymus. H372: Causes damages to the immune system through prolonged or repeated exposure. H400: Very toxic to aquatic life.
Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tradecanoate	10584-98-2	0.1-0.3%	Notified Classification: Germ Cell Mutagen Cat. 2, Acute Skin Toxicity Cat. 3, Acute Inhalation Toxicity Cat. 3, Acute Oral Toxicity Cat. 4, Skin Irritation Cat. 2, Skin Sensitization Cat. 1, Specific Target Organ Toxicity (Immune System, Thymus) Single Exposure Cat. 1, Aquatic Acute Toxicity Cat. 1 Hazard Statements: H341: Suspected of causing genetic effects. H311 + H331: Toxic in contact with skin or if inhaled. H317: May cause an allergic skin reaction. H371: May cause damage to immune system and thymus. H400: Very toxic to aquatic life. Hazards Not Otherwise Classified: Considered to be a PBT (Persistent, Bioaccumulative and Toxic) in the Environment) Compound
Quartz	14808-60-7	0.1-0.3%	Notified Classification: Carcinogen Category 1B, Specific Target Organ Toxicity (Inhalation-Lungs) Repeated Exposure Cat. 1 Hazard Statements: H350i: May cause cancer by inhalation. H372: Causes damages to organs through prolonged or repeated exposure.
Other components not classified, with no exposure limits and/or in less than 0.1% or those that do not add additional hazard to the product.		Balance	Classification: Not Applicable

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

4.1 PROTECTION OF FIRST AID RESPONDERS: Rescuers should not attempt to retrieve victims of exposure to this material without adequate personal protective equipment. Rescuers should be taken for medical attention, if necessary.

4.2 DESCRIPTION OF FIRST AID MEASURES: Remove victim(s) to fresh air, as quickly as possible. Only trained personnel should administer supplemental oxygen and/or cardio-pulmonary resuscitation, if necessary. Remove and isolate contaminated clothing and shoes. Seek immediate medical attention. Take copy of label and SDS to physician or other health professional with victim(s).

4.2.1 Inhalation: If aerosols of this material are inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions.

4.2.1.1 GHS Precautionary Statements for Inhalation Exposure: P304 + P340: If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing.

4.2.2 Skin Exposure: If the material contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 20 minutes. Do not interrupt flushing. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Victim must seek immediate medical attention.

4.2.2.1 GHS Precautionary Statements for Skin Exposure: P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P333 + P313: If skin irritation or rash occurs, get medical attention. P362 + P364: Take off contaminated clothing and wash it before reuse.

4.2.3 Eye Exposure: If this product enters the eyes, open victim's eyes while under gently running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 20 minutes. Do not interrupt flushing.

4.2.3.1 GHS Precautionary Statements for Eye Exposure: P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. P337 + P317: If eye irritation persists: get medical help.

4.2.4 Ingestion: If this material is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. Do NOT INDUCE VOMITING, unless directly by medical personnel. Have victim rinse mouth with water or give several cupfuls of water, if conscious. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration.

4.2.4.1 GHS Precautionary Statements for Ingestion Exposure: None.

4.3 MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Acute or chronic respiratory conditions may be aggravated by exposure to this product.

4.4 IMPORTANT SYMPTOMS AND EFFECTS, WHETHER ACUTE OR DELAYED: See Sections 2 (Hazard Identification) and 11 (Toxicological Information) for more detailed information.

4.4.1 Acute:

Symptoms/Effects: Fumes from heated product are an irritant to eyes and respiratory system. Direct eye contact may cause serious eye irritation. All potential effects are dependent on concentration and duration of exposure. May cause skin irritation.

Symptoms/Effects After Inhalation of Fumes or Aerosols: Inhalation may cause coughing, dry or sore throat, mucosal irritations, shortness of breath, respiratory system irritation.

Symptoms/Effects After Skin Contact: Dermatitis, dry skin, dermal irritation.

Symptoms/Effects After Direct Eye Contact: Moderate to severe irritation of eye tissue from direct eye contact. Aerosols may cause eye irritation.

Symptoms/Effects After Ingestion: Irritation of mucous membranes in the mouth, pharynx, esophagus and gastrointestinal tract.

4. FIRST-AID MEASURES

4.4 IMPORTANT SYMPTOMS AND EFFECTS, WHETHER ACUTE OR DELAYED (continued):

4.4.2 Chronic:

Symptoms/Effects After Skin Contact: Dermatitis (dry, red skin, itching, cracking of the skin, skin inflammation), allergic skin reaction.

Symptoms/Effects After Accidental Injection/Ingestion: None known.

Symptoms/Effects After Inhalation of Aerosols: None known.

Symptoms/Effects No Specific Route of Exposure: Potential carcinogenic, reproductive and/or mutagenic effects. May disrupt endocrine system and/or thymus.

4.5 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT IF NEEDED: Treat symptoms and eliminate exposure.

5. FIRE-FIGHTING MEASURES

5.1 **FLASH POINT:** > 93.3°C (> 200°F)

5.2 **AUTOIGNITION:** Not tested.

5.3 **FLAMMABLE LIMITS IN AIR:** Not tested.

5.4 **FIRE EXTINGUISHING MEDIA:** Use materials appropriate for surrounding materials. ABC extinguishers, carbon dioxide, foam, dry chemical and flooding quantities of water.

5.5 **UNSUITABLE EXTINGUISHING MEDIA:** None known.


5.6 **SPECIAL HAZARDS ARISING FROM THE PRODUCT:** Not sensitive to mechanical impact. Closed containers may develop pressure and rupture in event of fire.

5.6.1 **Explosion Sensitivity to Mechanical Impact:** Not sensitive.

5.6.2 **Explosion Sensitivity to Static Discharge:** Not expected to be sensitive.

5.7 **SPECIAL PROTECTIVE ACTIONS FOR FIRE-FIGHTERS:** Incipient fire

responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.



6. ACCIDENTAL RELEASE MEASURES

6.1 **PERSONAL PRECAUTIONS AND EMERGENCY PROCEDURES:** An accidental release may result in a fire. Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. Eliminate any possible sources of ignition and provide maximum explosion-proof ventilation. Use only non-sparking tools and equipment during the response. The atmosphere must at least 19.5 percent Oxygen before non-emergency personnel can be allowed in the area without Self-Contained Breathing Apparatus and fire protection. Avoid contact with water.

6.2 **PERSONAL PROTECTIVE EQUIPMENT:** Responders should wear the level of protection appropriate to the type of chemical released, the amount of the material spilled, and the location where the incident has occurred.

6.2.1 **Small Spills:** For releases of 1 drum or less, Level D Protective Equipment (gloves, chemical resistant apron, boots, and eye protection) should be worn.

6.2.2 **Large Spills:** Minimum Personal Protective Equipment should be rubber gloves, rubber boots, face shield, and Tyvek suit. Minimum level of personal protective equipment for releases in which the level of oxygen is less than 19.5% or is unknown must be **Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing and boots, hard hat, and Self-Contained Breathing Apparatus.**

6.3 **METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:**

6.3.1 **All Spills:** Eliminate all sources of ignition prior to spill response. Access to the spill area should be restricted. Spread should be limited by gently covering the spill with polypads. Absorb spilled liquid with clay, sand, polypads, or other suitable inert absorbent materials. All contaminated absorbents and other materials should be placed in an appropriate container and seal. Do not mix with wastes from other materials. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations). Dispose of recovered material and report spill per regulatory requirements. Remove all residue before decontamination of spill area. Clean spill area with soap and copious amounts of water. Monitor area for combustible vapor levels and confirm levels are below exposure limits given in Section 8 (Exposure Controls-Personal Protection), if applicable, and that levels are below applicable LELs (see Section 5 – Fire Fighting Measures) before non-response personnel are allowed into the spill area. Purge equipment with inert gas prior to reuse.

6.4 **ENVIRONMENTAL PRECAUTIONS:** Minimize use of water to prevent environmental contamination. Prevent spill or rinsate from contaminating storm drains, sewers, soil or groundwater. Place all spill residues in a suitable container and seal. Do not discharge effluent containing this product into streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

6. ACCIDENTAL RELEASE MEASURES (Continued)

6.5 OTHER INFORMATION: U.S. regulations may require reporting of spills of this material that reach surface waters if a sheen is formed. If necessary, the toll-free phone number for the US Coast Guard National Response Center is 1-800-424-8802.

6.6 REFERENCE TO OTHER SECTIONS: See information in Section 8 (Exposure Controls – Personal Protection) and Section 13 (Disposal Considerations) for additional information.

7. HANDLING and STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat or drink while handling this material. Avoid contact with eyes, skin, and clothing. Avoid breathing fumes, vapors or mist. Do not taste or swallow. Use only with adequate ventilation. Wash hands after handling this product. Contaminated clothing needs to be laundered prior to reuse. Keep away from heat and flame. In the event of a spill, follow practices indicated in Section 6: ACCIDENTAL RELEASE MEASURES. Keeping work areas clean is essential. Use work surfaces that can be easily decontaminated. Maintain good personal hygiene.

7.1.1 GHS Statements for Safe Handling: P203: Obtain, read and follow all safety instructions before use. P261: Avoid breathing vapors. P264 + P265: Wash hands and other contamination areas thoroughly after handling. Do not touch eyes. P270: Do not eat, drink or smoke when using this product. P271: Use only outdoors or in a well-ventilated area. P280: Wear protective gloves, clothing, eye protection and face protection.

7.2 CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITIES: Keep container tightly closed when not in use. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. Have appropriate extinguishing equipment in the storage area (such as sprinkler systems or portable fire extinguishers). Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Empty containers may contain residual product; therefore, empty containers should be handled with care. Store container below 27°C (80°F) to avoid possible reactions related to heat and overpressure of containers. This product is not compatible with oxidizing agents, acids, bases, alcohols, amines, amides, mercaptan, phenols.

7.2.1 GHS Statements for Safe Handling: P403 + P233 + P405: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

7.3 PRODUCT USE: This product is the base component for a self-leveling sealant. Follow all industry standards for use of this product.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

8.1 CONTROL PARAMETERS, INCLUDING OCCUPATIONAL EXPOSURE GUIDELINES OR BIOLOGICAL EXPOSURE LIMITS AND THE SOURCE OF THOSE VALUES:

8.1.1 Ventilation and Engineering Controls: Use with adequate, explosion proof ventilation to ensure exposure levels are maintained below the limits provided further in this section.

8.1.2 U.S. Occupational/Workplace Exposure Limits/Guidelines:

Chemical Name	CAS #	Guideline	Value
Calcium Carbonate (Limestone)	1317-65-3	ACGIH TLV TWA NIOSH REL TWA	15 mg/m ³ (total dust); 5 mg/m ³ (respirable fraction) 10 mg/m ³ (total dust); 5 mg/m ³ (respirable fraction)
Calcium Oxide	1305-78-8	ACGIH TLV TWA OSHA PEL TWA NIOSH STEL TWA DFG MAK TWA DFG MAK PEAK	2 mg/m ³ 5 mg/m ³ 2 mg/m ³ 1 mg/m ³ (inhalable fraction) 2•MAK; Excursion Factor: 1, 15 minutes average value, 4 per shift, 1-hr interval
Calcium Sulfates	Proprietary	ACGIH TLV TWA OSHA PEL TWA NIOSH STEL TWA DFG MAK TWA	10 mg/m ³ (inhalable fraction) 15 mg/m ³ (total dust); 5 (respirable fraction) 10 mg/m ³ (total dust); 5 (respirable fraction) 4 mg/m ³ (inhalable fraction); 1.5 mg/m ³ (respirable fraction)
Dibutyltin Dilaurate (Exposure limits given are for tetra-n-butyltin compounds)	77-58-7	DFG MAK TWA	0.004 mg/m ³ (can also be found as vapor); Skin (for n-butyltin compounds whose organic ligands are already designated 'Sa' or 'Sh,' these designations may also apply)
Ethyl Benzene	100-41-4	ACGIH TLV TWA OSHA PEL TWA NIOSH REL TWA NIOSH REL STEL NIOSH IDLH DFG MAK TWA DFG MAK PEAK DFG MAK Pregnancy Risk Classification	20 ppm (OTO) 100 ppm 100 ppm 125 ppm 800 ppm (10% of LEL) 20 ppm (skin) 2•MAK; Excursion Factor: 1, 15 minutes average value, 4 per shift, 1-hr interval (skin) C

See Section 16 for Definitions of Terms Used. OTO: Ototoxicant

8. EXPOSURE CONTROLS - PERSONAL PROTECTION (Continued)

8.1 CONTROL PARAMETERS, INCLUDING OCCUPATIONAL EXPOSURE GUIDELINES OR BIOLOGICAL EXPOSURE LIMITS AND THE SOURCE OF THOSE VALUES (continued):

8.1.2 U.S. Occupational/Workplace Exposure Limits/Guidelines (continued):

Chemical Name	CAS #	Guideline	Value
2-Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (Exposure limits given are for tetra-n-butyltin compounds)	10584-98-2	DFG MAK TWA DFG MAK PEAK	0.002 mg/m ³ (can also be found as vapor); Skin (for n-butyltin compounds whose organic ligands are already designated 'Sa' or 'Sh,' these designations may also apply 1•MAK; Excursion Factor: 1, 15 minutes average value, 4 per shift, 1-hr interval
Quartz (Crystalline Silica) [continued]	14808-60-7	OSHA PEL TWA NIOSH REL TWA NIOSH REL STEL	0.005 mg/m ³ (respirable dust); 1/2 the value calculated from the respirable dust formulae for Quartz** 0.005 mg/m ³ (respirable dust); See NIOSH Pocket Guide Appendix A See NIOSH Pocket Guide Appendix A **This standard applies to any operations or sectors for which the Respirable crystalline silica standard, 1910.1053, is stayed or is otherwise *Respirable dust 14464-46-1 not in effect.
Soda Lime Glass (as synthetic vitreous fibers special purpose glass fibers)	65997-17-3	ACGIH TLV TWA	1 fiber per cubic centimeter (Respirable fibers. Length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400–450x magnification (4-mm objective), using phase-contrast illumination)
Stearate Exposure limits given are for stearates	Proprietary	ACGIH TLV TWA	10 mg/m ³ (inhalable fraction); 3 mg/m ³ (respirable fraction)
Titanium Dioxide	13463-67-7	ACGIH TLV TWA OSHA PEL TWA NIOSH STEL TWA	0.2 mg/m ³ (respirable fraction) finescale particles 15 mg/m ³ (total dust) See Pocket Guide Appendix A
Xylene	1330-20-7	ACGIH TLV TWA ACGIH TLV STEL OSHA PEL TWA OSHA PEL STEL NIOSH REL TWA NIOSH REL STEL NIOSH IDLH	100 ppm 150 ppm 100 ppm 150 ppm (vacated 1989 PEL) 100 ppm 150 ppm 900 ppm

See Section 16 for Definitions of Terms Used.

8.1.3 Biological Exposure Indices (BEIs): Currently, the following BEI's have been established for some components.

CHEMICAL: DETERMINANT	SAMPLING TIME	BEI
Ethyl Benzene • Sum of Mandelic Acid and Phenylglyoxylic Acid in Urine	• End of Shift	• 0.15 g/g Creatinine
Xylenes • Methylhippuric Acid in Urine	• End of Shift	• 0.15 g/g Creatinine

8.2 INDIVIDUAL PROTECTION MEASURES, SUCH AS PERSONAL PROTECTIVE EQUIPMENT: The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132, including the Respiratory Protection Standard (29 CFR 1910.134), Eye Protection Standard 29 CFR 1910.13, the Hand Protection Standard 29 CFR 1910.138, and the Foot Protection Standard 29 CFR 1910.136), equivalent standards of Canada (including the Canadian CSA Respiratory Standard Z94.4-93-02, the CSA Eye Protection Standard Z94.3-M1982, Industrial Eye and Face Protectors and the Canadian CSA Foot Protection Standard Z195-M1984, *Protective Footwear*). Please reference applicable regulations and standards for relevant details.

8.2.1 Eye/Face Protection: Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations.

8.2.2 Skin Protection: Wear chemical impervious gloves (e.g., Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations.

8.2.3 Body Protection: Use body protection appropriate for task (e.g., lab coat, coveralls, Tyvek suit). If necessary, refer to the OSHA Technical Manual (Section VII: Personal Protective Equipment) or appropriate Standards of Canada. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in appropriate regulations.

8.2.4 Respiratory Protection: If mists or sprays from this product are created during use, use appropriate respiratory protection. If necessary, use only respiratory protection authorized in appropriate regulations. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under appropriate regulations.

9. PHYSICAL and CHEMICAL PROPERTIES

9.1 FORM: Smooth sealant.

9.2 COLOR: Various colors.

9.3 MOLECULAR WEIGHT: Mixture.

9.4 MOLECULAR FORMULA: Mixture.

9.5 ODOR: Mild.

9.6 ODOR THRESHOLD: Not determined.

9.7 BOILING POINT: Not available.

9. PHYSICAL and CHEMICAL PROPERTIES (Continued)

- 9.8 **FREEZING/MELTING POINT:** Not available.
- 9.9 **RELATIVE DENSITY/SPECIFIC GRAVITY (water = 1):** 1.10
- 9.10 **VAPOR DENSITY: (air = 1):** > 1
- 9.11 **VAPOR PRESSURE:** Not available.
- 9.12 **pH:** Not available.
- 9.13 **SOLUBILITY IN WATER:** Not soluble.
- 9.14 **OTHER SOLUBILITIES:** Not known.
- 9.15 **EVAPORATION RATE (nBuAc = 1):** Not available.
- 9.16 **VOLATILE ORGANIC COMPOUNDS (VOC):** Not available.
- 9.17 **FLAMMABILITY:** Not flammable.
- 9.18 **FLASH POINT:** > 93.3°C (> 200°F)
- 9.19 **AUTOIGNITION TEMPERATURE:** Not determined.
- 9.20 **FLAMMABLE LIMITS IN AIR:** Not tested.
- 9.21 **PERCENT VOLATILE BY VOLUME:** < 20 g/L
- 9.22 **COEFFICIENT WATER/OIL DISTRIBUTION:** Not available.
- 9.23 **VISCOSITY:** Not available.
- 9.24 **HOW TO DETECT THIS SUBSTANCE (WARNING PROPERTIES):** The viscous form of this product may act as a warning property in the event of an accidental release.
-

10. STABILITY and REACTIVITY

- 10.1 **REACTIVITY:** This product is not known to be reactive under normal circumstances of use and handling.
- 10.2 **CHEMICAL STABILITY:** Stable under normal circumstances of use and handling.
- 10.3 **POSSIBILITY OF HAZARDOUS REACTIONS/POLYMERIZATION:** Not determined. Due to the trace isocyanate component, there may be a slight hazard of polymerization in contact with amines or other incompatible materials.
- 10.4 **CONDITIONS TO AVOID:** Avoid contact with incompatible chemicals and exposure to ignition sources, prolonged heating or extreme temperatures.
- 10.5 **INCOMPATIBLE MATERIALS:** This product is not compatible with oxidizing agents, acids, bases, alcohols, amines, amides, mercaptan, phenols.
- 10.6 **HAZARDOUS DECOMPOSITION PRODUCTS:**
- 10.6.1 **Combustion:** Thermal decomposition of this product can generate calcium, carbon, potassium, sodium, silicon, titanium and nitrogen oxides, acetaldehyde, furan, dioxolane, carbon, hydrogen cyanide and formaldehyde.
- 10.6.2 **Hydrolysis:** None known.
-

11. TOXICOLOGICAL INFORMATION

- 11.1 **POTENTIAL HEALTH EFFECTS:** The most significant routes of occupational exposure are contact with skin and eyes. The symptoms of exposure to this product are as follows:
- 11.1.1 **Contact with Skin:** Causes skin irritation. Depending on the duration of skin contact, skin exposure can cause reddening, discomfort or irritation. Contains multiple compounds that may cause skin sensitization and allergic reaction in susceptible individuals. Symptoms can include reddening of skin, rash, welts and itching. Once sensitized, exposure to very small amount can cause reactions.
- 11.1.1.1 **Contact with Eyes:** Although unlikely due to the form of the product, direct eye contact may cause serious eye irritation. Contact with fumes from heated product and the eyes can cause irritation, reddening and watering.
- 11.1.1.2 **Skin Absorption:** Prolonged skin contact may be harmful by skin absorption as described under ingestion or inhalation.
- 11.1.1.3 **Ingestion:** Although ingestion is unlikely in the workplace, if swallowed, irritation of the mouth, throat, and other tissues of the gastro-intestinal system can occur, as well as cause nausea, vomiting, and diarrhea.
- 11.1.1.4 **Inhalation:** Effects by inhalation are not likely to the paste form of the product. If heated to decomposition, inhalation of fumes may cause respiratory irritation. Inhalation of fumes may irritate the tissues of the nose, mouth, throat, and upper respiratory system. Symptoms of exposure may include coughing, sneezing, and difficulty breathing. Contains a trace component that may cause respiratory sensitization and allergic reaction.
- 11.1.1.5 **Injection:** Accidental injection of this product (e.g., puncture with a contaminated object) may cause burning, redness, and swelling in addition to the wound.
- 11.1.1.6: **Other Effects:**
- Ethyl Benzene:** In workplace studies involving solvent mixtures containing ethylbenzene isomers, there was a significant increase in inner ear disorders in comparison with unexposed controls; Ethyl Benzene is considered an ototoxicant, especially by repeated inhalation.
- Dibutyltin Dilaurate:** The trace Dibutyltin Dilaurate component has exhibited moderate acute toxicity when given orally to rodents and induced effects in the liver. Repeated oral administration to rodents caused damage to the gastro-intestinal tract and liver and caused central nervous system effects.
- 11.2 **DELAYED and IMMEDIATE EFFECTS and CHRONIC EFFECTS FROM SHORT-TERM and LONG-TERM EXPOSURE:**
- 11.2.1 **Short-Term:** Direct eye contact may cause irritation. Skin contact and inhalation aerosols may be irritating. Ingestion may be harmful.
- 11.2.2 **Long-Term:** Prolonged or chronic skin contact may cause dermatitis or skin sensitization, respiratory sensitization and allergic reaction in susceptible individuals. Repeated inhalation exposure to the trace Ethyl Benzene component poses a significant hazard of damage to the inner ear. Chronic exposure may cause adverse effects on the liver, kidneys, thymus and endocrine system. Chronic exposure may pose a hazard of carcinogenic, reproductive and mutagenic effects.
-

11. TOXICOLOGICAL INFORMATION (Continued)

11.3 TARGET ORGANS:

- 11.3.1 **Short Term:** Skin, eyes, respiratory system.
 11.3.2 **Long Term:** Skin, liver, kidneys, thymus, hearing organs.

11.4 OVERALL ACUTE TOXICITY ESTIMATES (ATE) FOR PRODUCT:

- 11.4.1 **Oral ATE:** > 4400 mg/kg (< 12% unknown)
 11.4.2 **Dermal ATE:** > 3400 mg/kg (24% unknown)
 11.4.3 **Inhalation Vapor ATE:** Not possible to calculate due to high percentage of unknown toxicity (> 74%)

11.5 TOXICITY DATA: The following toxicology data are available for components greater than 1% in concentration. Due to the large amount of data, only human data, LD50 Oral-Rat or Mouse, LD50 Skin-Rat or Mouse, LC50 Inhalation-Rat or Mouse and skin irritation data are provided in this SDS. Contact Pecora for more information.

Calcium Carbonate (Limestone):

LD₅₀ (Oral-Rat) 2000 mg/kg
 LC₅₀ (Inhalation-Rat) 4 hours: > 3.26 mg/L

Calcium Oxide:

LD₅₀ (Oral-Rat) > 2000 mg/kg
 LD₅₀ (Skin-Rabbit) > 2500 mg/kg
 LC₅₀ (Inhalation-Rat) 4 hours: > 6.04 mg/L

Calcium Sulfates:

LD₅₀ (Oral-Rat) > 2000 mg/kg
 LD₅₀ (Skin-Rabbit) 2000 mg/kg
 LC₅₀ (Inhalation-Rat) 4 hours (dust): > 3.26 mg/L

Proprietary Phthalate:

LD₅₀ (Oral-Rat) > 5000 mg/kg
 LD₅₀ (Skin-Rabbit) > 20,000 mg/kg

Proprietary Prepolymer:

LD₅₀ (Oral-Rat) > 5000 mg/kg
 LD₅₀ (Skin Rat) > 2000 mg/kg
 LC₅₀ (Inhalation-Rat) 1 hour: > 0.17 mg/L (no deaths)

Silicones and Siloxanes:

Standard Draize Test (Eye-Rabbit) 500 mg: Mild
 LD₅₀ (Oral-Rabbit) > 2000 mg/kg

Soda Lime Glass:

Oral & Skin: E-glass microfibre is inorganic, highly insoluble and stable to hydrolysis. This fiber has low potential to cross biological membranes and consequently has a low potential for absorption through the gastrointestinal tract or via the skin.

Soda Lime Glass (continued):

Inhalation: Testing of acute inhalation toxicity is waived because results from long-term inhalation toxicity studies are available. Based on these long-term inhalation studies E-glass microfibre is evaluated to have no acute toxicity by inhalation.

Xylenes:

Standard Draize Test (Eye-Human) 200 ppm
 LDLo (Oral-Human) 50 mg/kg
 LCLo (Inhalation-Human) 10,000 ppm/6 hours: Behavioral: general anesthetic; Lungs, Thorax, or Respiration: cyanosis; Blood: other changes
 TCLo (Inhalation-Human) 200 ppm: Sense Organs and Special Senses (Olfaction): effect, not otherwise specified; Sense Organs and Special Senses (Eye): conjunctive irritation; Lungs, Thorax, or Respiration: other changes
 Standard Draize Test (Skin-Rabbit) 100%: Moderate
 Standard Draize Test (Skin-Rabbit) 500 mg/24 hours: Moderate
 Standard Draize Test (Eye-Rabbit) 87 mg/L: Mild
 Standard Draize Test (Eye-Rabbit) 5 mg/24 hours: Severe
 Open Irritation Test (Skin-Rat) 60 uL/8 hours: Mild
 LD₅₀ (Oral-Rat) 4300 mg/kg: Liver: other changes; Kidney/Ureter/Bladder: other changes
 LD₅₀ (Skin-Rabbit) > 1700 mg/kg
 LC₅₀ (Inhalation-Rat) 4 hours: 5000 ppm

11.6 REPEATED DOSE TOXICITY:

2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol: Repeated dose toxicity testing via oral route has shown systemic effects (target organ) digestive: liver; urogenital: kidneys. Based on the data, the test substance has to be classified for specific target organ toxicity - repeated exposure (STOT RE): Cat. 2.

Dibutyltin Dilaurate: Based multiple repeated dose toxicity tests, Dibutyltin Dilaurate showed adverse effects on the thymus and immune system. The substance is assigned to Single Exp. Category 1 based on test results which indicate 50% reduction of thymus weight following a single oral dose of 18 mg/kg. Signal word: Danger; Hazard statement: H370 Causes damage to thymus.

Ethyl Benzene: When there is repeated exposure by inhalation, irreversible damage of auditory function and of sensory cells of the cochlea is a serious health concern. After 13 weeks of exposure minimal effects were still observed at 200 ppm (0.88 mg/l) and the NOEC was extrapolated to 114 ppm (0.5 mg/l). According to EU CLP (Regulation (EC) No. 1272/2008) and UN GHS the NOAEC of 0.5 mg/l is within the classification limit of 0.2-1 mg/l/6h/d for STOT-RE Cat. 2 leading to a classification with H 373: causes damage to the auditory system through prolonged or repeated inhalative exposure.

Sodium Lime Glass: Studies on the bio-persistence of Sodium Lime-glass microfibre indicate that accumulation of fibres occur with repeated inhalation exposure (See endpoint 7.12). Studies in endpoint 7.5 on repeated exposure by inhalation show that E-glass microfibre is able to induce inflammation and fibrosis in the lung, with a LOAEC of 15 WHO fibres/ml air (Bellman et al 2003).

Titanium Dioxide: Titanium dioxide did not show any adverse effects oral repeated dose toxicity studies. Titanium dioxide is not absorbed to any relevant extent through human skin; thus, no toxic effects can be expected via the dermal route of exposure. Titanium dioxide showed adverse pulmonary effects in chronic inhalation studies only at concentrations above the maximum tolerated dose (MTD).

11.7 CARCINOGENIC POTENTIAL: The following table summarizes the carcinogenicity listing for the components of this product. "NO" indicates that the substance is not considered to be or suspected to be a carcinogen by the listed agency, see section 16 for definitions of other ratings.

CHEMICAL	IARC	EPA	NTP	NIOSH	ACGIH	OSHA	PROP 65
Ethyl Benzene	2B	D	No	No	A3	No	No
Quartz/Crystalline Silicas	1	No	K*	Ca	A2	No	Yes (airborne particles of respirable size)
Stearic Acid (as a stearate compound)	No	No	No	No	A4	No	No
Soda Lime Glass (as glass wool fibers)	2B	No	R (inhalable fraction)	No	A3	No	Yes (inhalable)
Titanium Dioxide	2B	No	No	Ca	A3	No	Yes (airborne particles of respirable size)
Xylene	3	I	No	No	A4	No	Yes

ACGIH TLV-A2: Human data are accepted as adequate in quality but are conflicting or insufficient to classify the agent as a confirmed human carcinogen; or the agent is carcinogenic in experimental animals at dose(s), by route(s) of exposure, at site(s), of histologic type(s), or by mechanism(s) considered relevant to worker exposure. ACGIH TLV-A3: Confirmed Animal Carcinogen with Unknown Relevance to Humans. ACGIH TLV-A4: Not Classifiable as a Human Carcinogen. EPA-D: Not Classifiable as to Human Carcinogenicity. EPA-I: Data are Inadequate for an Assessment of Human Carcinogenic Potential. IARC-1: Carcinogenic to Humans. IARC-2B: Possibly Carcinogenic to Humans. IARC-3: Unclassifiable as to Carcinogenicity in Humans. NIOSH-Ca: Potential Occupational Carcinogen with no Further Categorization. NTP-R (Reasonably Anticipated to Be a Human Carcinogen). NTP-K: Known to Be a Human Carcinogen * Respirable Fraction

11. TOXICOLOGICAL INFORMATION (Continued)

11.7 CARCINOGENIC POTENTIAL (continued):

11.7.1 Additional Information on Carcinogenic Potential:

Soda Lime Glass: Studies on the bio-persistence of Sodium Lime-glass microfibre indicate that accumulation of fibres occur with repeated inhalation exposure (See endpoint 7.12). Studies in endpoint 7.5 on repeated exposure by inhalation show that E-glass microfibre is able to induce inflammation and fibrosis in the lung. In conclusion E-glass microfibre is classified Carc. Cat. 2; R49 (may cause cancer by inhalation) according to DSD-DPD. According to GHS it is classified as Carc 1B, H350i.

Distillates (Petroleum) Solvent Dewaxed Heavy Paraffinic: The EU ECHA carcinogenic classification of Carcinogenic Cat. 1B is based upon the presence of 3% or more of DMSO. As this cannot be verified by the supplier, this classification applies to this product.

11.8 IRRITANCY OF PRODUCT: This product is irritating by skin exposure. Aerosols may be irritating to the respiratory system and eyes. Direct eye contact may cause more serious irritation.

11.9 SENSITIZATION TO THE PRODUCT: Multiple components have been classified as skin sensitizers as indicated below.

11.9.1 Skin Sensitization: The following information is available for the components that have been found to have skin sensitizing effects.

bis(1,2,2,6,6-pentamethyl-4-piperdyl) Sebacate: Based upon skin sensitization tests (*in vivo* (non-LLNA) 70% of the animals were sensitized by the test compound under the experimental conditions employed, this compound meets the criteria of Category 1A (indication of significant skin sensitizing potential) under GHS.

Dibutyltin Dilaurate: Based multiple repeated dose toxicity tests, Dibutyltin Dilaurate showed adverse effects on the thymus and immune system. The substance is assigned to Single Exp. Category 1 based on test results which indicate 50% reduction of thymus weight following a single oral dose of 18 mg/kg. Signal word: Danger; Hazard statement: H370 Causes damage to thymus.

Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tetradecanoate: In a dermal sensitization study according to OECD 406, 10 week old male and female Pirbright White Guinea Pigs were exposed to TK 11638/1 in a maximization test. The test substance was found to be sensitizing according to GHS and should therefore be classified as H317 - May cause sensitization by skin contact.

Methyl 1,2,2,6-pentamethyl-4-piperdiyl Sebacate: Suspected Skin Sensitizer: CAESAR skin sensitization model in VEGA (Q)SAR platform predicts that the chemical is Sensitizer (good reliability).

11.9.2 Respiratory Sensitization: The following information is available on respiratory sensitization effects from components. This product contains a trace isocyanate compound. In persons who are sensitive to isocyanates, cross-sensitization to other isocyanates can occur.

p-Toluene sulfonylisocyanate: This compound has been given a GHS classification of Respiratory Sensitizer Cat. 1, H334; no specific data is available.

11.10 ENDOCRINE TOXICITY: The Dibutyltin Dilaurate and Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tetradecanoate compounds are organic dibutyltin compounds. Organic tin compounds are considered to be endocrine disruptors and may cause adverse effects on the thymus gland.

11.11 TOXICOLOGICAL SYNERGISTIC PRODUCTS: There have been several studies in humans and animals on the interaction of Xylenes with drugs, alcohol and other solvents. Xylene has a high potential to interact with other compounds because it increases metabolic enzymes in the liver and decreases metabolic enzymes in the lungs. In general, exposure to related solvents, such as benzene, toluene and ethanol (alcohol) slows the rate of clearance of Xylenes from the body, thus enhancing its toxic effects.

11.12 REPRODUCTIVE TOXICITY INFORMATION: This product has not been tested for reproductive toxicity.

11.12.1 Mutagenicity: No component of this product is known to cause human mutagenic effects. The following information is available for components.

Dibutyltin Dilaurate: Based upon *in vivo* and *in vitro* mutagenicity testing and positive results, this compound is classified as having mutagenic properties. According to Regulation (EC) no 1272/2008 the test substance would be classified as Muta. 2 with the Hazard statement: H341: Suspected of causing genetic defects and should be accompanied with the signal word 'Warning'.

Ethylbenzene: Ethylbenzene was found to induce forward mutations in mouse lymphoma cells at 80 mg/L without metabolic activation; this concentration was near the lethal concentration of 100 mg/L. However, other *in vitro* testing has shown that Ethylbenzene does not induce mutagenicity. Although notified EU ECHA classification gives Ethylbenzene a Germ Cell Mutagen classification, review of data is not conclusive to mutagenicity.

Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tetradecanoate: Based upon *in Vivo* mutagenicity testing and positive results, this compound is classified as having mutagenic properties. According to Regulation (EC) no 1272/2008 the test substance would be classified as Muta. 2 with the Hazard statement: H341: Suspected of causing genetic defects and should be accompanied with the signal word 'Warning'.

Quartz/Crystalline Silica: ECHA Properties of Concern: Suspected Mutagen: The outcome in CTA assay is positive according to ISSCTA.

11.12.2 Embryotoxicity/Teratogenicity: No component of this product is known to cause human embryotoxic/teratogenic effects. The following information is available for components.

Xylene (mixed isomers) are considered fetotoxic in humans, based on observations of reduced fetal weight, delayed ossification and persistent behavioral effects in animal studies in the absence of maternal toxicity. Several human population studies have suggested a link between exposure to organic solvents (including xylene) and increased occurrence of miscarriages or birth defects in children. However, in the majority of cases, there was exposure to a variety of solvents at the same time, exposure was ill-defined, and the number of cases examined was small.

11.12.3 Reproductive Toxicity: No component has been classified as a reproductive toxin.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

12.1 MOBILITY: This product has not been tested for mobility in soil.

12.2 PERSISTENCE AND BIODEGRADABILITY: This product has not been tested for persistence or biodegradability.

Several trace compounds are suspected as being persistent and or non-biodegradable.

2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol: Considered to be a PBT (Persistent, Bioaccumulative and Toxic) in the Environment Compound. Under Assessment as a POP (Persistent Organic Pollutant) Compound

Methyl 1,2,2,6-pentamethyl-4-piperdiyl Sebacate: Listed by the EU ECHA database as: Suspected Persistent in the Environment: The Danish QSAR database contains information indicating that the substance is predicted as non-readily biodegradable.

12. ECOLOGICAL INFORMATION (Continued)

12.3 BIO-ACCUMULATION POTENTIAL: This product has not been tested for bio-accumulation potential. Multiple trace components are suspected as having bio-accumulation potential.

2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol: Considered to be PBT (Persistent, Bioaccumulation and Toxic in the Environment).

Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tetra-decanoate: Considered to be PBT (Persistent, Bioaccumulation and Toxic in the Environment).

12.4 ECOTOXICITY: This product has not been tested for aquatic or animal toxicity. All release to terrestrial, atmospheric and aquatic environments should be avoided. The following aquatic toxicity data are presented for components present a significant toxic hazard to aquatic organisms.

bis(1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate:

LC₅₀ (*Danio reio* Zebra fish) 96 hours: 0.97 mg/L

EC₅₀ (*Daphnia magna* Big water flea) 24 hours: 1 mg/L

EC₅₀ (*Desmodesmus subspicatus* Green algae) 72 hours: 1.68 mg/L

Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stanna-tetradecanoate:

LC₅₀ (*Brachydanio reio* Zebra fish) 96 hours: 7.2-19.0 mg/L

LC₅₀ (*Daphnia magna* Giant water flea) 48 hours: > 1.4 mg/L

Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stanna-tetradecanoate (continued):

EC₅₀ (*Desmodesmus subspicatus* Green algae) 48 hours: 0.44-0.7 mg/L

Methyl 1,2,2,6,6,-Pentamethyl-4-Piperidyl Sebacate:

LC₅₀ (*Lepomis macrochirus* Bluegill) 96 hours: 0.9 mg/L

LC₅₀ (*Daphnia magna* Giant water flea) 21 days: 1 mg/L

EC₅₀ (*Desmodesmus subspicatus* Green algae) 72 hours: 1.68 mg/L

12.4.1 GHS Statements for Environmental Hazards: P273: Avoid release to the environment.

12.5 OTHER ADVERSE EFFECTS: This product is not expected to have any ozone depletion potential.

12.6 ENDOCRINE DISRUPTORS: The Dibutyltin Dilaurate and Ethylhexyl 4,4-dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-4-stannate-tetradecanoate compounds are organic dibutyltin compounds. Endocrine disruptors that find their way into the environment can cause adverse effects on aquatic and terrestrial organisms.

12.7 ENVIRONMENTAL EXPOSURE CONTROLS: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

13. DISPOSAL CONSIDERATIONS

13.1 PREPARING WASTES FOR DISPOSAL: As supplied, this product is not a hazardous waste as defined by U.S. federal regulation (40 CFR 261) if discarded or disposed. State and local regulations may differ from federal regulations. The generator of the waste is responsible for proper waste determination and management.

13.1.1 GHS Statements for Disposal: P501: Dispose of contents/containers in accordance with all local, regional, national and international regulations.

13.2 U.S. EPA WASTE NUMBER: None applicable.

14. TRANSPORTATION INFORMATION

14.1 U.S. DEPARTMENT OF TRANSPORTATION (DOT): Not regulated per U.S. DOT regulations, under 49 CFR 172.101.

14.2 TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS (TDG): Not regulated per regulations of Transport Canada.

14.3 INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): Not regulated per the International Air Transport Association.

14.4 INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): Not regulated per the International Maritime Organization.

15. REGULATORY INFORMATION

15.1 U.S. REGULATIONS:

15.1.1 U.S. SARA Reporting Requirements: The following components of this product are subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

CHEMICAL	SECTION 302 EHS (TPQ) (40 CFR 355, Appendix A)	SECTION 304 RQ (40 CFR Table 302.4)	SECTION 313 TRI (threshold) (40 CFR 372.65)
Ethylbenzene	No	No	Yes
Proprietary Prepolymer (as a glycol ether)	No	No	Yes (as glycol ether)
Xylene	No	No	Yes

Proprietary Prepolymer: As a glycol ether, is subject to Section 313 TRI (Threshold) (40 CFR 372.65)

15.1.2 U.S. SARA Hazard Categories (Section 311/312, 40 CFR 370-21): ACUTE: Yes; CHRONIC: Yes; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

15.1.3 U.S. TSCA Inventory Status: All components of this product listed by CAS# in Section 3 are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

15.1.4 U.S. CERCLA Reportable Quantity (RQ): Ethylbenzene: 1000 lb (454 kg); Xylene: 100 lb (45.4 kg). As a glycol ether compound, the Proprietary Prepolymer component is a CERCLA Hazardous Material, although it has no specific reportable quantity.

15.1.5 U.S. Clean Air Act (CA 112r) Threshold Quantity (TQ): The Ethylbenzene and Xylene components are listed as a Hazardous Air Pollutants (HAPs) generally known or suspected to cause serious health problems. The Clean Air Act, as amended in 1990, directs EPA to set standards requiring major sources to sharply reduce routine emissions of toxic pollutants. EPA is required to establish and phase in specific performance-based standards for all air emission sources that emit one or more of the listed pollutants. The above compounds are included on this list.

15. REGULATORY INFORMATION (Continued)

15.1.6 U.S. Clean Water Act Requirements: Xylenes (mixed) are designated as a hazardous substance under section 311(b)(2)(A) of the Federal Water Pollution Control Act and further regulated by the Clean Water Act Amendments of 1977 and 1978. These regulations apply to discharges of these substance. This designation includes any isomers and hydrates, as well as any solutions and mixtures containing this substances.

15.1.7 California Safe Drinking Water And Toxic Enforcement Act (Proposition 65): Benzene-1-chloro-4-fluoromethyl, Ethyl Benzene and Glass Wool Fibers (inhalable and bio-persistent) are listed on the California Proposition Lists. **WARNING:** This product can expose you to chemicals including Benzene-1-chloro-fluoromethyl and Ethyl Benzene which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to P65Warnings.ca.gov. In addition, to the warning text provided above, the following symbol must be displayed. Where the sign, label or shelf tag for the product is not printed using the color yellow, the symbol may be printed in black and white. The symbol shall be placed to the left of the text of the warning, in a size no smaller than the height of the word "WARNING".



The Quartz (Crystalline Silica) and Titanium Dioxide components are listed on the Proposition 65 lists, but only as airborne, unbound particles of respirable size, which is not applicable to this product. As such, the Proposition 65 warning for these compounds is not applicable to this product.

15.2 CANADIAN REGULATIONS:

15.2.1 Canadian DSL/NDSL Inventory Status: The components of this product are on the DSL Inventory.

15.2.2 Canadian Environmental Protection Act (CEPA) Priorities Substances Lists: The Xylene component is on the CEPA Priority Substances 1 List, not considered as "TOXIC" under Section 64 of CEPA. As organic tin compounds, the trace Dibutyltin Dilaurate and 2-Ethylhexyl 4,-Dibutyl-10-ethyl-7-oxo-8-oxa-3,5-dithia-stannatetradecanoate components are also listed on the Priority Substances 1 List.

15.2.3 Canadian WHMIS (HPR-GHS) 2015 Classification and Symbols: See Section 16 in Classification and Symbols under HPR-GHS 2015.

16. OTHER INFORMATION

16.1 HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS®)

Health	2*
Flammability	1
Physical Hazard	0

See Section 16 for definitions of ratings

0 = Minimal 3 = Serious
1 = Slight 4 = Severe
2 = Moderate * = Chronic

HMIS® is a registered trademark of the National Paint and Coatings Association.

16.2 REFERENCES AND DATA SOURCES: Contact the supplier for information.

16.3 METHODS OF EVALUATING INFORMATION FOR THE PURPOSE OF CLASSIFICATION: Bridging principles were used to classify this product.

16.4 DATE OF PREPARATION: October 30, 2023

16.5 REVISION DETAILS: New.

16.6 DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information presented in this Safety Data Sheet is presented in good faith based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale.

All materials may present hazards and should be used with caution. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices or applicable federal, state, or local laws or regulations. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

16. OTHER INFORMATION (Continued)

16.2 DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on an SDS. Some of these, which are commonly used, include the following:

KEY ACRONYMS:

CHEMTREC: Chemical Transportation Emergency Center, a 24-hour emergency information and/or emergency assistance to emergency responders.

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

IDLH: Immediately Dangerous to Life and Health. This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL" is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV: Threshold Limit Value. An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

WEEL: Workplace Environmental Exposure Limits from the AIHA.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD: 0 Minimal Hazard: No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. Mechanical irritation may occur. PII or Draize = 0. *Eye Irritation:* Essentially non-irritating, minimal effects clearing in < 24 hours. Mechanical irritation may occur. Draize = 0. *Oral Toxicity LD₅₀ Rat:* > 5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 2000 mg/kg. *Inhalation Toxicity 4-hrs LC₅₀ Rat:* > 20 mg/L. **1 Slight Hazard:** Minor reversible injury may occur; may irritate the stomach if swallowed; may defat the skin and exacerbate existing dermatitis. *Skin Irritation:* Slightly or mildly irritating. PII or Draize > 0 < 5. *Eye Irritation:* Slightly to mildly irritating, but reversible within 7 days. Draize > 0 ≤ 25. *Oral Toxicity LD₅₀ Rat:* > 500–5000 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 1000–2000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 2–20 mg/L. **2 Moderate Hazard:** Temporary or transitory injury may occur; prolonged exposure may affect the CNS. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. PII or Draize ≥ 5, with no destruction of dermal tissue. *Eye Irritation:* Moderately to severely irritating; reversible corneal opacity; corneal involvement or irritation clearing in 8–21 days. Draize = 26–100, with reversible effects. *Oral Toxicity LD₅₀ Rat:* > 50–500 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 200–1000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.5–2 mg/L. **3 Serious Hazard:** Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may cause destruction of dermal tissue, skin burns, and dermal necrosis. PII or Draize > 5–8, with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. *Oral Toxicity LD₅₀ Rat:* > 1–50 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* > 20–200 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.05–0.5 mg/L. **4 Severe Hazard:** Life-threatening; major or permanent damage may result from single or repeated exposure; extremely toxic; irreversible injury may result from brief contact. *Skin Irritation:* Not appropriate. Do not rate as a 4, based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a 4, based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L.

FLAMMABILITY HAZARD: 0 Minimal Hazard: Materials that will not burn in air when exposure to a temperature of 815.5°C (1500°F) for a period of 5 minutes. **1 Slight Hazard:** Materials that must be pre-heated before ignition can occur. Material requires considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur. This usually includes the following: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C (200°F) (e.g., OSHA Class IIIB); and Most ordinary combustible materials (e.g., wood, paper, etc.).

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

FLAMMABILITY HAZARD (continued): 2 Moderate Hazard: Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres with air. This usually includes the following: Liquids having a flash-point at or above 37.8°C (100°F); Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g., cotton, sisal, hemp); and Solids and semisolids (e.g., viscous and slow flowing as asphalt) that readily give off flammable vapors. **3 Serious Hazard:** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions. This usually includes the following: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 38°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (e.g., OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air (e.g., dusts of combustible solids, mists or droplets of flammable liquids); and Materials that burn extremely rapidly, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). **4 Severe Hazard:** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and that will burn readily. This usually includes the following: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (e.g., OSHA Class IA); and Materials that ignite spontaneously when exposed to air at a temperature of 54.4°C (130°F) or below (pyrophoric).

PHYSICAL HAZARD: 0 Water Reactivity: Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No 0 rating. *Unstable Reactives:* Substances that will not polymerize, decompose, condense, or self-react. **1 Water Reactivity:** Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable but can become unstable at high temperatures and pressures. These materials may react with water but will not release energy violently. *Explosives:* Division 1.5 & 1.6 explosives. Substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III oxidizers; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose condense, or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosion hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors. **2 Water Reactivity:** Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 explosives. Explosive substances where the explosive effects are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group II oxidizers. Solids: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential (or low risk) for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature.

16. OTHER INFORMATION (Continued)

16.2 DEFINITIONS OF TERMS (continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

PHYSICAL HAZARD (continued): 3 Water Reactivity: Materials that may form explosive reactions with water. **Organic Peroxides:** Materials that are capable of detonation or explosive reaction but require a strong initiating source or must be heated under confinement before initiation; or materials that react explosively with water. **Explosives:** Division 1.3 explosives. Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. **Compressed Gases:** Pressure \geq 514.7 psi absolute at 21.1°C (70°F) [500 psig]. **Pyrophorics:** No Rating. **Oxidizers:** Packing Group I oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. Liquids: any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. **Unstable Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a moderate potential (or moderate risk) to cause significant heat generation or explosion. **4 Water Reactivity:** Materials that react explosively with water without requiring heat or confinement. **Organic Peroxides:** Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. **Explosives:** Division 1.1 & 1.2 explosives. Explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. **Compressed Gases:** No Rating. **Pyrophorics:** Add to the definition of Flammability 4. **Oxidizers:** No 4 rating. **Unstable Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion. **Pyrophorics:** Add to the definition of Flammability 4. **Oxidizers:** No 4 rating. **Unstable Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 2000 mg/kg. Materials with an LD₅₀ for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin. **1** Materials that, under emergency conditions, can cause significant irritation. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD₅₀ for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg. **2** Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. **3** Materials that, under emergency conditions, can cause serious or permanent injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 1,000 ppm but less than or equal to 3,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials corrosive to the skin. Cryogenic gases that cause frostbite and irreversible tissue damage. Compressed liquefied gases with boiling points below -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials with an LD₅₀ for acute oral toxicity greater than 5 mg/kg but less than or equal to 50 mg/kg. **4** Materials that, under emergency conditions, can be lethal. Gases with an LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than ten times its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D of NFPA 704. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in accordance with Annex D of NFPA 704. Liquids, solids, and semisolids having a flash point at or above 93.4°C (200°F) (e.g., Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the *Method of Testing for Sustained Combustibility*, per 49 CFR 173, Appendix H or the UN *Recommendations on the Transport of Dangerous Goods, Model Regulations* (current edition) and the related *Manual of Tests and Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85% by weight. Liquids that have no fire point when tested by ASTM D 92, *Standard Test Method for Flash and Fire Points by Cleveland Open Cup*, up to the boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Most ordinary combustible materials. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (e.g., Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures with air.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

FLAMMABILITY HAZARD (continued): 2 (continued): Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal, and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (e.g., Class IB and IC liquids). Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g., dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (e.g., Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100 W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater.

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point:** Minimum temperature at which a liquid gives off sufficient vapor to form an ignitable mixture with air near the surface of the liquid or within the test vessel used. **Autoignition Temperature:** Minimum temperature of a solid, liquid, or gas required to initiate or cause self-sustained combustion in air with no other source of ignition. **LEL:** Lowest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame. **UEL:** Highest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. **LD₅₀:** Lethal Dose (solids & liquids) that kills 50% of the exposed animals. **LC₅₀:** Lethal Concentration (gases) that kills 50% of the exposed animals. **ppm:** Concentration expressed in parts of material per million parts of air or water. **mg/m³:** Concentration expressed in weight of substance per volume of air. **mg/kg:** Quantity of material, by weight, administered to a test subject, based on their body weight in kg. **TDLo:** Lowest dose to cause a symptom. **TCLo:** Lowest concentration to cause a symptom. **TD₀, LDLo, and LDo:** or **TC, TC₀, LCLo, and LCo:** Lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** **IARC:** International Agency for Research on Cancer. **NTP:** National Toxicology Program. **RTECS:** Registry of Toxic Effects of Chemical Substances. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI:** ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REPRODUCTIVE INFORMATION:

A **mutagen** is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An **embryotoxin** is a chemical that causes damage to a developing embryo (e.g., within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance that interferes in any way with the reproductive process.

ECOLOGICAL INFORMATION:

EC: Effect concentration in water. **BCF:** Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. **TLM:** Median threshold limit. **log K_{OW}** or **log K_{OC}:** Coefficient of Oil/Water Distribution is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S.:

EPA: U.S. Environmental Protection Agency. **ACGIH:** American Conference of Governmental Industrial Hygienists, a professional association that establishes exposure limits. **OSHA:** U.S. Occupational Safety and Health Administration. **NIOSH:** National Institute of Occupational Safety and Health, which is the research arm of OSHA. **DOT:** U.S. Department of Transportation. **TC:** Transport Canada. **SARA:** Superfund Amendments and Reauthorization Act. **TSCA:** U.S. Toxic Substance Control Act. **CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act. Marine Pollutant status according to the DOT; CERCLA or Superfund; and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

CANADA:

WHMIS: Canadian Workplace Hazardous Materials Information System. **IC:** Transport Canada. **DSL/NDSL:** Canadian Domestic/Non-Domestic Substances List.